

20-21-1W

FORMATION RECORD

Give detailed description and thickness of all formations drilled through and contents of sand, whether dry, water, oil or g.

| Formation | Top | Bottom | Formation | Top | Bottom |
|---------------------|------|--------|----------------------------------|-----|--------|
| Surface Clay & Sand | 0 | 25 | | | |
| Shale & Shells | 25 | 141 | | | |
| Lime | 141 | 144 | | | |
| Shale & Shells | 144 | 466 | Set 136' 6" of 10" Csg. | | |
| Shale & Lime Shells | 466 | 591 | @ 144' and cemented with | | |
| Shale & Lime Shells | 591 | 600 | 150 sacks Ash Grove Cement | | |
| Shale & Shells | 600 | 650 | | | |
| Broken Lime | 650 | 878 | | | |
| Shale & Shells | 878 | 1436 | | | |
| Lime | 1436 | 1476 | | | |
| Shale & Shells | 1476 | 1736 | | | |
| Lime | 1736 | 1839 | | | |
| Shale | 1839 | 1874 | | | |
| Broken Lime | 1874 | 2118 | | | |
| Shale & Shells | 2118 | 2134 | | | |
| Shale | 2134 | 2200 | | | |
| Lime | 2200 | 2267 | | | |
| Shale | 2267 | 2302 | | | |
| Lime | 2302 | 2658 | | | |
| Shale & Lime Shells | 2658 | 2706 | | | |
| Broken Lime | 2706 | 2739 | | | |
| Lime & Shale | 2739 | 2763 | | | |
| Shale & Shells | 2763 | 2800 | | | |
| Shale | 2800 | 2890 | | | |
| Chat | 2890 | 3020 | | | |
| Lime | 3020 | 3085 | | | |
| Broken Lime | 3085 | 3119 | | | |
| Lime | 3119 | 3184 | | | |
| Shale | 3184 | 3257 | | | |
| Lime - Hunton | 3257 | 3302 | Set 3282' 7" of 7" OD Csg. @ | | |
| Shale | 3302 | 3303 | 3259 and cemented with 300 sacks | | |
| | | | Victor Cement. | | |
| | | | Show of oil 3259-3264' | | |
| | | | Hole filled up 400' with oil | | |
| | | | from 3264' to 3269'. | | |
| | | | 1000' oil in hole from 3269' to | | |
| | | | 3274'. | | |
| | | | 2000' oil in hole from 3274' | | |
| | | | to 3279'. | | |

