


57773

B. & R. DRILLING Co.
 Ira No. 1.

SEC. 13 T. 21 R. 11 W.
 NEc SE

Total Depth. 3426 P.B. 3384
 Com. 12-21-41 Comp. 1-3-42
 Shot or Treated.
 Contractor. B. & R. Drilling.
 Issued. 2-28-42

County Stafford.



CASING.

8" 248 cemented.
 5 1/2" 3368'

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

sand	110	lime	2625
red sdy shale	180	shale and sholls	2680
red rock	415	lime	2720
anhydrite	435	lime and shalo	2780
shale shells	835	lime	2920
shale blue	880	lime and shale	3047
red rock	892	lime	3149
shale blue and shells	1150	shale and sholls	3175
shale and shells	1200	lime	3528
shale and salt	1240	cherty congl.	3333
lime	1250	cherty congl.	3373
shalo and sholls	1270	corod 3373- 3383	
lime	1355		
anhydrite	1410	10' Coro 7' roc.	
brkn lime	1460	1 1/2' sand	
red shale	1480	5 1/2" groaso shalo.	
lime	1565		
lime and shells	1615	shalo	3413
lime	1670	Arbuckle lime	3426
lime and shalo	1690	Total Depth.	
sdv lime	1720		
lime and shale	1800	Saturation . 3358-64	
lime	1820	Some Saturatod in sand.	
lime and shale	1875		
lime	1940		
lime & shalo	2020		
lime	2060	cemented back to 3384	
shalo & sholls	2325	Pipe perforatod 3358-64	
broken lime	2335		
lime	2385		
broken lime	2390		
shale and shells	2500		
sand	2600		