SIDE ONE

5152 5112	
Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa days after the completion of a well, regardless of he	s 67202, within thirty (30) ow the well was completed.
Attach separate letter of request if the inform If confidential, only file one copy. Information on record and Side Two will then be neld confidential. Applications must be made on dual completion, complete the confidential of the completion of the complete that the completion of the complete that	Side One will be of public
injection and temporarily abandoned wells. Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	ical log, sonic log, gamma ray
LICENSE # 5313 EXPIRATION DATE	
OPERATOR F & M OIL CO., INC.	
ADDRESS 422 Union Center	COUNTY Stafford
Wichita, Kansas 67202	
	PROD. FORMATION
PHONE (316)262-::636	
PURCHASER	LEASE Salem "G"
ADDRESS Union Drilling Co. Inc.	WELL NO
	WELL LOCATION N/2 NE NE
DRILLING Union Drilling Co., Inc.	330 Ft. from North Line and
ADDRESS 422 Union Center	660 Ft. from East Line of
Wichita, Kansas 67202	the NE (Qtr.)SEC2 TWP21S RGE 12W.
PLUGGING Union Drilling Co., Inc.	WELL PLAT (Office
CONTRACTOR ADDRESS 422 Union Center	Use Only) KCC
Wichita, Kansas 67202	KGS
TOTAL DEPTH 3445' PBTD	SWD/REP
SPUD DATE 10-5-82 DATE COMP; ETED 10-14-82	PLG
ELEV: GR 1824' DF 1831' KB 1834'	
DRILLED WITH (CABLE) (ROTARY) (1.13) TOOLS.	
DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE	
mount of surface pipe set and cemented 278' w/250	DV Tool Used? None .
THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas, S Injection, Temporarily Abandoned, OWWO. Other	Shut-in Gas, Dry, Disposal,
ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATION AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	ONS PROMULGATED TO REGULATE THE OIL
<u>A FIDAVIT</u>	
	ing of lawful age, hereby certifies
that:	5.,

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit.

The statements and allegations contained therein are true and correct.

SIDE TWO

OPERATOR F & M OIL CO., INC. LEASE Salem "G" #1 SEC. 2 TWP21S RGE 12W

ACO-1 WELL HISTORY

FILL IN WELL LOG AS REQUIRED:

Show all important zones of porosity and contents tilereof; cored intervals, and all drill-stem tests, in- cluding depth interval tested, cushion used, time tool spen, flowing and shut-in pressures, and recoveries.			SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.		
FORMATION DESCRIPTION, CONTENTS, E.C.	ТОР	воттом	NAME	DEPTH	
DST#1 3152-3190',			Sample Tops:		
30-303-30-30, wk 12" blow, rec 40' mud	1		Topeka	2735 (- 901	
FP's 44-46#, SIP's 44-43#.			Heebner	3012(-1178	
-1 0 11 10 N D 11 B 11 15 H.			Toronto	3029 (-1195	
DST#2 3192-3230',			Douglas Sh	3043(-1209	
30-45-30-45, wk blow, rec 30' mud w/		l	Br/Lime	3146 (-1312	
show of oil, FP's 44-54#, SIP's 892-848#	ŧ		Lansing	3156 (-1322	
	•		B/KC	3387(-1553	
DST#3 3280-3295',	·		Arbuckle	3418(-1584	
30-45-30-45, wk 14" blow, rec 10' mud			RTD	3445 (-1611	
w/show of oil, FP's 35-35#, S::P's 35-					
35#.			Electric Log '	ops:	
			Anhydrite	588 (+1246	
DST#4 3301-3323',			B/Anhydrite	609 (+1225	
30-45-60-45, fr blow, rec 110 watery			Topeka	2734(- 900	
mud, FP's 65-70#, SIP's 848-793#.			Heebner	3013(-11	
			Toronto	3028(-1194)	
DST#5 3336-3350',			Douglas Sh	3042(-1208)	
30-45-60-45, wk blow on 1st orn bldg			Br/Lime	3146 (-1312)	
to ga blow on 2nd opn, rec 24(GTP.			Lansing	3156 (-1322)	
30' slight O&GCM w/show of free oil			B/KC	3390 (-1556)	
in tool, IFP 44-35#, ISIP 134#, FFP 44-			Arbuckle	3419 (-1585)	
37#, FSIP 88#, BHT 102°.			LTD	3447(-1613)	
i					
DST#6 3388-3420',					
30-45-30-45, wk 18" blow, rec 10' mud	1				
W/spks of oil, FP's 44-66#, SIP's 88-	l				
50#.	i				
. i					
DST#7 3389-3425',					
30-45-60-45, wk steady blow on 1st opn,					
wk decreasing blow on 2nd opn, rec 40'	· ·			_	
slight GCM w/show of free oil in top					
of tool, IFP's 55-55#, ISIP's 165#					
FFP's 44-44#, FSIP's 66#, BHT 104°.					
·					
Report of all strings set surface, intermediat:, production, etc.	CASING RE	CORD (No.	w) or (Used)	_	
nopon or on annual terms burnedly intermediately, production, etc.	CAJING KE	COND (ME)	w) or (usea)		

Purpose of string	Size hole drilled	Sixe casing +t (in O.D.)	∵′eight lbs/ft.	Setting depth	Type cement	Socks	Type and percent additives
Surface	12½"	8-5/٤"	20#	278'	common	250	2% gel, 3% (

LINER RECORD		PERFORATION RECORD				
Top, ft.	Bottom, ft.	Sack : cement	Shots per ft.	Size & type	Depth interval	
;	TUBING RECORD					
Size	Setting depth	Pack or set at				

OPERATOR

F & M OIL CO., INC. LEASE NAME Salem "G" #1# SEC. 2 TWP. 215 RGE. 12W

FILL IN WELL LCG AS REQUIRED: Show ell important zones of porosity and contents the eof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool of the flowing and shut-in pressures, and recoveries.			SHOW GEOLOGICAL MARKERS, LOGS I OR OTHER DESCRIPTIVE INFORMAT	
FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM		
DST#8 3425-3435', 30-30-30-30, vry wk blow diec in 20", flushed tool on 2nd opn, no help, rec 940' GIP, 15' drlg mud, IFP &8-55#, ISIP 171#, FFP 88-66#, FSIP 161#, BHT				
105°.				1
DST#9 3435-3445', Miss-run, packer seat failure.				
DST#10 3425-3445', 30-45-60-45, wk blow trhoughout test, rec 50' drlg mud w/show of free oil in tool, IFP 88-77#, ISIP 353#, FFP 66 FSIP 243#.	- 66#,			
·		ĺ		
	ļ ·			
			"	
			·	
			·	
			-	
				1