WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bank Bldg, Wichita, Kansas.

2 - 21 - 13W

CARTER OIL CO.
V. Andross No. 1.

SEC 2 T. 21 R. 13W.
CSL N½ N½ SE
440' S of Center of N.L.

Total Depth. 3608
Comm. 1-5-38 Comp. 2-21-38
Shot or Treated. 1000 gal 3535-3554
Contradtor.
Issued. 3-12-38

MAR 1 2 1938

County. Stafford. Platted



Elevation.

Production. DRY.

CASING.

85/8" 258' 4½" 3535'

Figures Indicato Bottom of Formations.

| | |
|---|---|
| sand gravel | 150 |
| shale | 175 |
| sand | 230 |
| shale | 265 |
| rod bed | 465 |
| shale red | 700 |
| anhydrite | 725 |
| red shale shells | 835 |
| shale red&blue | 970 |
| shale shells | 1200 |
| salt | 1383 |
| shale shells | 1400 |
| lime | 1420 |
| shale shells | 1430 |
| lime | 1470 |
| shale shells | 1505 |
| broken lime | 1551 |
| lime | 1670 |
| broken lime shale | 1690 |
| sdy lime | 1702 |
| lime | 1770 |
| shale shells | 1795 |
| lime | 1805 |
| shale shells | 1825 |
| sdy lime | 1868 |
| lime | 1875 |
| shale | 1885 |
| sdy lime | 1912 |
| shale shells | 1940 |
| shale lime shells | 1985 |
| lime | 1995 |
| shale shells | 2012 |
| shale | 2027 |
| lime | 2045 |
| shale lime shells | 2115 |
| lime | 2198 |
| lime shale | 2237 |
| lime | 2248 |
| broken lime | 2274 |
| lime | 2312 |
| shale shells | 2600 |
| lime shale brks | 2632 |
| lime | 2664 |
| broken lime shale | 2696 |
| lime | 2715 |
| lime | 2920 |
| shale | 2924 |
| lime shale shells | 2970 |
| lime | 3019 |
| shale shells | 3036 |
| lime | 3120 |
| shale green | 3125 |
| shale | 3149 |
| lime | 3167 |
| shale | 3255 |
| lime | 3287 |
| cored lime | 3301 |
| lime | 3475 |
| shale chert | 3484 |
| shale | 3490 |
| conglomerate | 3498 |
| cored conglomerate | 3503 |
| conglomerate | 3527 |
| dolomite | 3531 |
| cored dolomite | 3534 |
| cored siliceous lime | 3539 |
| cored Siliceous | 3554 |
| siliceous | 3608 |

Total Depth.

Arbuckle 3535-3608

Top Kansas City Lans. 3255
Rainbow show oil 3285-89
Rainbow show oil 3339-40
Oil stain 3410-15
Rainbow show oil 3415-17
Very small show oil 3435-40 & 62-65
Top Basal Penn. Cgl. 3475
Top Decorah 3527 Good show oil 3527-29
Top Siliceous lime 3535.
1 BWPHR 3577-78
300' water in 24 hours 3588
300' water 4 hrs. 3603-08

| | |
|---|---|
| shale shells | 2770 |
| lime | 2781 |
| lime shale breaks | 2821 |
| shale shells | 2835 |
| lime | 2861 |
| broken lime shale | 2872 |