
22-21-13W

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company. D. R. Lauck Oil Company Inc.,
Farm. Schulz "C" No. 3

SEC. 22 T. 21 R. 13W.
SE SW SE

County Stafford.
KANSAS



Total Depth. 3735'
Comm. 10-9-57 Comp. 10-28-57
Shot or Treated.
Contractor. Lauck Drilling Co.,
Issued. 1-11-58

CASING:
10 3/4" @ 240' w/200 sks. cem.
7" @ 3735' w/125 sks. cem.

Elevation. 1874' DF.

Production. 25 BOPD.

Figures Indicate Bottom of Formations

clay & sand	90
shale & sand	200
shale	290
sand	310
red bed & shale	720
shale & shells	1600
lime & shale	1660
lime	1920
shale & lime	1965
lime	2065
shale & lime shells	2200
shale & lime	2475
shale & shells	2615
shale & lime	2815
lime	3235
shale (Douglas)	3304
lime (Brown)	3536
chert	3562
lime & shale	3578
lime	3735 RTD
Total Depth.	

TOPS:

Heebner	3175	3177
Toronto	3195	3196
Douglas Shale	3209	3210
Brown Lime	3304	3304
Lansing Kansas City	3316	3316
Base Kansas City	3537	3538
Cherty Conglomerate	3556	3556
Viola	3567	3568
Simpson	3597	3598
Arbuckle	3653	3654
Rotary Total Depth	3735	3735

Drill Stem Test:

1# (M-D) 3318-31 open 1 hr. strong blow 1 hr. rec. 1050' gas and 30' slighty gas cut mud. FFP 0# BHP

2# (M-D) 3335-50 Open 1 hr. strong blow 1 hr. gas in 6 mins. 62,000 CFS 10 mins. 44,000 in 20 mins. rec. 3135' gassy oil and flowed by heads; IFP 190# FFP 510# BHP 1120# in 20 mins.

3# (S) 3654-60 open 1 hr. weak blow 1 hr. Rec. 1250' gas and 32' very slightly oil cut mud; FP 0# BHP 120# in 20 mins.

4# (S) 3660-65 open 1½ hrs; weak blow 1½ hrs; gas to surface in 20 mins. Rec. 60' oil cut mud 30' muddy oil, 30' gassy oil; IFP 0# FFP 200# BHP 1360# in 20 mins.

5# (S) 3665-75 open 1 hr. good blow 1 hr. gas to surface in 12 mins. Rec. 100' gas and oil cut mud, 55' muddy gassy oil with some free oil; IFP 120#, FFP 230# BHP 1200# in 20 mins.

6# (M-D) 3675-3690 open 1½ hrs; good blow 1½ hrs; Rec. 1025' gassy salt water with trace of oil IFP 0#; FFP 425#; BHP 840# in 20 mins.