

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 10-1-87
month day year

API Number 15—

OPERATOR: License # 5210
 Name Lebsack Oil Production, Inc.
 Address P.O. Box 489
 City/State/Zip Hays, Ks. 67601
 Contact Person Wayne Lebsack
 Phone 316-938-2396

CONTRACTOR: License # 5422
 Name Abercrombie Drilling Co.
 City/State Wichita, Ks.

Well Drilled For: Well Class: Type Equipment:
☒ Oil ☐ SWD ☐ Infield ☒ Mud Rotary
☒ Gas ☐ Inj ☒ Pool Ext. ☐ Air Rotary
☐ OWWO ☐ Expl ☐ Wildcat ☐ Cable

If OWWO: old well info as follows:

Operator
 Well Name
 Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 6/19/87 Signature of Operator or Agent Title Operator

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required feet per Alt. 1 2

This Authorization Expires Approved By

NW NW/4 Sec. 18 Twp. 21 S, Rg. 34 East
 4470' Ft. from South Line of Section
 1680' Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 600' feet

County Finney

Lease Name Foster Well # 1-18

Ground surface elevation 3010' est. feet MSL

Domestic well within 330 feet: yes no

Municipal well within one mile: yes no

Depth to bottom of fresh water 250

Depth to bottom of usable water 1200

Surface pipe by Alternate: 1 2 X

Surface pipe planned to be set 350'

Conductor pipe required

Projected Total Depth 4900' feet

Formation Miss. - Morrow

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 2255'	feet depth with 50/sx	sxs of Poz. 60/40
2nd plug @ 1338'	feet depth with 50/sx	sxs of Poz. 60/40
3rd plug @ 455'	feet depth with 50/sx	sxs of Poz. 60/40
4th plug @ 40' solid brg	feet depth with 10/sx	sxs of Poz. 60/40
5th plug @ 15	feet depth with	sxs of
(2) Rathole with 15 sxs		(b) Mousehole with sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging.
 In Addition: Call district office after well is either plugged or production casing is cemented in.

(Call 7 a.m. to 5 p.m. workdays)

District office use only:

API #15—

Surface casing of feet set with sxs at hours, 19

Alternate 1 or 2 surface pipe was used.

Alternate 2 cementing was completed @ ft. depth with sxs on, 19

Hole plugged, 19, agent