


4-22-12W

MARYLYN OIL CO.
 Sittner No. 1.

SEC. 4 T. 22 R. 12 W
 SWc NW

Total Depth. 3682' DFM
 Comm. 9-15-43 Comp. 10-3-43
 Shot or Treated.
 Contractor. Tri-State Drlg.Co., Inc.
 Issued. 11-6-43

County. Stafford



CASING:
 8 5/8" 260' Cem.
 5 1/2" 3673' DFM Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

cellar	6
sand	220
red bed	335
red bed - shale	670
anhydrite	690
red rock, shale, shells	740
shale & shells	1250
salt & shale	1385
shale-shells	1480
anhydrite	1553
sdv lime & shale	1670
lime & shale	1785
lime, shale strks	1845
lime sdv	1880
sand sharp	1930
shale	2015
lime & shale	2205
shale & shells	2365
shale & lime	2595
lime brkn	2685
lime & shale	2730
lime brkn & shale	2820
lime & shale	2870
lime	2925
lime brkn	2990
lime brkn-shale	3040
shale & lime	3135
lime	3230
lime brkn	3250
shale & lime strks	3325
lime	3550
shale-lime	3575
conglomerate cherty	3605
lime	3627
shale	3673
Arbuckle lime	3675
cored	3680
lime	3683
Total Depth. (DFM 3682)	

Viola	3600
Simpson	3626
Arbuckle	3672
Cored	3674-3679
recovered	4 1/2'
Total Depth	3683 (DFM 3682)
bailing wtr	

Tops: Lansing 3326 DFM
 Base Kansas City 3550
 Congl.Cherty 3562