

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- VICKERS PETROLEUM CO., INC.
Farm- Curtis "A" No. 4

SEC. 6 T. 22 R. 13W
NW NW SW NW
Approx. 1585' NL, 330' WL

Total Depth. 3615'
Comm. 2-16-54 Comp. 3-9-54
Shot or Treated.
Contractor.
Issued. 4-24-54

County Stafford
KANSAS



CASING:

8 5/8" 340' cem w/275 sx
5 1/2" 3615' cem w/150 sx

Elevation. 1919' KB
(4' above G. L.)
Production. Pmp. 71 BOPD, NW Pot.

Figures indicate Bottom of Formations.

sand	200
shale & sand	300
red rock & red beds	340
red beds & sand	797
anhydrite	820
shale & shells	945
shale & lime	1355
shale & salt	1580
lime & shale	1850
lime	2008
lime & shale	2350
shale & lime	2485
lime & shale	2690
shale & lime	2815
lime & shale	2998
lime	3241
black shale	3246
lime	3249
shale	3261
lime	3273
shale	3365
lime	3368
shaley lime	3373
shale	3377
lime	3599
shale	3604
lime	3609
shale	3615
Total Depth	

Tops:	Schlumberger	Sample
Heebner	3240	3241
Toronto	3260	3261
Douglas	3273	3273
Brown Lime	3364	3365
Lansing	3376	3377

Acidize w/1000 gas. Swab 5 BOPH.