WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bk Bldg., Wichita, Kansas.

STANOLIND OIL & GAS CO.
G. A. Schilling No. 1.

SEC. 12 T. 22 R. 13W
SE SE NW
330' N SL 2310' E WL

Total Depth. 3716'
Comm. 11-29-37 Comp. 12-30-37
Shot or Treated. 2000 & 3000 Gals.
Contractor.
Issued. 2-26-38

Rotary 0-3708
Cable 3708-16

County. Stafford

CASING:
13" 250'6"
6" 3702'9"



Elevation.

Production. Pot. 47 B.
10% Wtr.

Figures Indicate Bottom of Formations.

sand	190	Shooting
sand & hrd rock	225	20 Qts. sand tamped 3716
red bed	785	
red bed & shale blue	1045	Acidizing
salt shale & lime shells	1516	2000 & 3000 Gals.
brkn lime	1545	
lime	1753	Siliceous lime 3703-3716
shale & shells	1790	
lime	1838	Swabbed 4½ bbls oil per hr. after acidizing.
brkn lime	2050	
shale & lime shells	2102	Eight-hr state potential 47 B., 10% wtr.
lime & shells	2204	
brkn lime	2246	
Steel line Corr 2246-2242		
brkn lime	2566	
shale & shells	2675	
brkn lime	2910	
shale & lime	2940	
Topeka lime-Top 2940-92		
lime	3042	
lime & shale break	3114	
lime	3203	
brkn lime	3265	
shale	3302	
shale & shells	3375	
Top Lansing 3375		
lime	3460	
lime grey dense	3465	
shale grey	3470	
lime tan dense	3474	
brkn lime	3515	
lime	3572	
brkn lime & shale	3612	
shale	3620	
chert	3656	
shale & shells	3695	
Core #2 7½' Recovery		
shale green	3702	
shale green sdy w/GSO	3704	
Top Siliceous lime 3703		
Core #3 2½' Recovery		
dolomite - cherty & shaley with good sh oil	3708	
Cable Tool Record		
lime	3712	
lime drk hrd	3714	
cherty lime-sm sh oil-	3716	
Total Depth.		