
WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas 15-22-25W

Company. KEWANEE OIL CO.
Farm. Kline No. 3

SEC. 15 T. 22 R. 25W
NE NW NE
330' fr NL, 978.67' fr WL of the NE/4

Total Depth. 4642' PB 4597'
Comm. 2-3-59 Comp. 2-20-59
Shot or Treated.
Contractor. Graham-Michaelis Drlg. & K & A Drlg.
Issued. 4-25-59

County Hodgeman
KANSAS



CASING:
8 5/8" 550.40' cem w/350 sx.
5 1/2" 4634.10' cem w/100 sx.
2 3/8" 4594.37' (O.D. Tubing)

Elevation. 2467' CM

Production. 93 BOPD

Figures Indicate Bottom of Formations.

surface	0
surface soil	100
shale & lime shells	470
shale	1060
shale & gyp	1141
sand	1335
shale & sand	1645
lime	1858
lime & shale	3974
lime	4060
lime & shale	4081
lime	4523
lime & chert	4642 RTD
Total Depth	
Plugged back to 4597'	

TOPS: SAMPLE	C.M. MEAS.
Heebner	3861
Toronto	3877
Douglas	3898
Lansing-Kansas City	3910
Base Kansas City	4310
Marmaton	4340
Conglomerate	4538
Mississippi	4562

TOPS: SCHLUMBERGER	C.M. MEAS.
Heebner	3862
Toronto	3878
Douglas	3898
Lansing-Kansas City	3912
Base Kansas City	4310
Marmaton	4341
Conglomerate	4537
Mississippi	4562

Treating Record: Acidized w/250 gals. Mud-Sol by B J Service Co.

Perforating Record: Perforated from 4570' to 4580' C.M. w/4 bullets per foot by FGAC.