

22-22-25W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- KEWANEE OIL CO.
Farm- Redet No. 1

SEC. 22 T. 22 R. 25W
NE NE NW
330' fr NL, 330' fr EL
of NW/4

Total Depth. 4706' PB 4674.5'
Comm. 5-26-59 Comp. 6-8-59
Shot or Treated.
Contractor. Graham-Michaelis Drlg.
Issued. 9-19-59

County Hodgeman
KANSAS



Elevation. 2520' CM

Production. 4 BOPD

CASING:

8 5/8" 112.29' cem w/100 sx.
5 1/2" 4705.31' cem w/375 sx.
DV Tool @ 1984.64'
2 3/8" Tubing @ 4668.19'

Figures indicate Bottom of Formations.

surface	0
surface clay & sand	115
shale	330
sand	435
shale	740
red bed	935
red bed & shale	1217
sand	1402
sand & shale	1585
shale & shells	1915
shale	2050
shale & shells	2370
shale & lime	2750
lime	3096
lime & shale	3680
lime	4504
cherty lime & shale	4616
lime & chert	4625
Mississippi lime	4662
lime & chert	4675
lime	4706
Total Depth	

TOPS: SAMPLE C.M. MEAS.

Heebner	3914
Toronto	3933
Douglas	3956
Lansing-Kansas City	3968
Base Kansas City	4374
Cherokee	4504
Conglomerate	4596
Mississippi	4617

TOPS: SCHLUMBERGER C.M. MEAS.

Heebner	3916
Toronto	3934
Douglas	3957
Lansing-Kansas City	3970
Base Kansas City	4374
Cherokee	4504
Conglomerate	4596
Mississippi	4622
Spergen-Warsaw	4690

Treating Record: 6-18-59 Acidized w/500 gallons 15% MCA.
6-19-59 Acidized w/1000 gallons 15% acid.
6-21-59 Acidized w/2000 gallons 15% acid, w/45 balls.

Perforating Record: 6-17-59 perforated 4640-4642' w/4 jets/ft.
6-17-59 perforated 4634-4640' w/4 jets/ft.
6-17-59 perforated 4629-4634' w/4 bullets/ft.