

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY

UNION NATIONAL BANK BLDG WICHITA, KANSAS

Location, NWc NW SW
330' NL 330' WL, SW¹/₄

Sec. 8 T. 22 R. 3W.


Casing Record,

County, Harvey

10" Farm, M. Androes
20" 8" 3171 Company, The Texas Company,
15 1/2" 65/8" 3435 Contr, Trigg Drilling Co.
12 1/2" 284 53/16" Comm. 10-3-33
Total Depth, 3618' Shot Quarts Between,
Correspondence Regarding This Well Should Be Referred To.

No. 3

Comp 12-8-33



Elevation.

Figures Indicate Bottom of Formations,
Date Issued, 1-6-34

Initial Production,
Pumped 1st 17 hours 155 B.

Formation	Depth	Formation	Depth.
surface	97	lime grey hard	2799
shale	150	lime white hard	2807
shale and lime shells	190	lime grey hard	2827
shale sticky	240	shale blue med	2832
sand	255	shale blk med	2867
shale and shells	284	lime grey med	2900
shale and shells dark soft	366	lime grey hard	2910
shale blue soft	390	shale	2920
gyp rock white med	490	lime white hard	2931
lime and sand grey hard	517	lime grey soft	2953
lime white hard	585	shale blk hard	2990
sdv lime	667	shale blue med	3023
shale and shells white med blue	700	shale blk med	3090
lime white hard	720	slate blue med	3125
shale blue med	777	shale blk med	3142
shale and lime shells dk med	891	lime white hard	3148
lime grey hard	950	shale and shells dark med	3156
No log	995	chat white hard	3170
shale and shells blue med	1176	chat white soft	3173
sdv shale grey med	1236	chat white hard	3185
shale and shells blue soft	1322	chat white hard	3190
shale blue soft	1440	chat white hard	3212
sdv shale grey med	1520	lime small sh gas	3185 3245
shale and lime shells dk soft	1622	lime brown small sh oil	3190 3325
lime grey hard	1642	shale blk	3335
shale blue soft	1680	shale grey	3435
shale blue med	1760	sdv lime white hard	3452
lime grey hard	1770	sdv lime brown soft sh oil	3454
shale and lime shells dark med	1861	sdv lime brown hard	3475
shale and lime shells hard	1916	slate dark med	3515
shale blue hard	1963	shale dark soft	3582
lime white hard	1983	lime white hard	3605
shale dark hard	2017	sand grey hard	3615
lime grey hard	2057	sand grey soft	3618
sand shell white hard	2062	TD.	SLM
lime white hard	2073		
shale and shells blue hard	2092	Hole reduced to 5" at 3589.	
lime white hard	2112	700' water and Rainbow oil	
lime grey hard	2145	3615-3618	
lime white med	2160	Plugged back to 3595 with lead wool	
shale blue med	2184	and rock plugged back from 3595 to	
lime white med	2225	3590 with Guiberson Bottom/hole plug.	
lime grey hard	2232	Cemented back from 3595 to 3485.	
lime grey med	2285	Lead wool. from 3485 to 3479.	
shale and shells blue med	2336		
shale blk	2421		
lime white hard	2430	Top chat 3156	
shale blue and red rock	2458	Base lime 3325	
shale blue hard	2500	Top Hunton 3435	
lime white hard	2525	Base Hunton 3475	
lime brown hard	2685	Top Viola 3582	
shale blk soft	2700	Base Viola 3605	
sdv lime brown med	2715	Wilcox 3605-3618	
shale blue med	2723		
lime white hard	2768		
lime grey med	2785		

Rotary from 0 to 3173.
Cable from 3173 to 3618

Size of shot, quarts 300G. Acid 700G. wtr
Top of shot 3450
Bottom of shot 3477