

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas


28-23-12W

THE TEXAS CO.
M. Gerdes No. 1.

SEC.28 T.23 R.12W
NW NE SW

Total Depth. 3852'
Comm. 6-6-41 Comp. 7-3-41
Shot or Treated. 500 Gals. Acid
Contractor. Warren & Bradshaw Drilg. Co.
Issued. 8-2-41 Rotary O-3848
Cable 3848-52

County. Stafford



CASING:
10 $\frac{3}{4}$ " 336' Cem.
5 $\frac{1}{2}$ " 3848' Cem.

Elevation.

Production. Pot. 4105 B.

Figures Indicate Bottom of Formations. No wtr, Depth.

surface	250	5 $\frac{1}{2}$ " csg was cemented at
reamed	372	3848' and perforated back
sand & red bed	830	to 3832', oil from 3832
shale & sand	950	to T.D.
gyp & shells	953	
shale & gyp	1130	
gyp	1145	
shale, lime, sand	1450	
shale & lime	1605	
lime	1825	
shale & lime	1920	
lime hrd	2025	
lime & shale	2125	
lime	2260	
shale & limo	2300	
lime	2348	
limo brkn	2393	
shale blue	2440	
lime brkn	2560	
shale & limo	2720	
lime	2767	
limo & shale	2925	
lime hrd	2950	
shale, str. chert	3000	
lime hrd	3010	
shale	3020	
lime hrd	3042	lime 3603
lime & shale	3190	brkn lime & shale 3610
lime hrd	3214	lime hrd 3623
shale	3220	lime 3665
lime hrd	3243	shale & lime 3704
shale & lime hrd	3269	lime & chert 3710
limo & shale	3372	lime & chert hrd 3737
sticky shale & shells	3383	lime & chert 3760
shale & shells	3423	lime & sharp chert hd 3786
brkn lime & shale	3450	lime 3795
lime brkn	3524	brkn lime & shale 3824
shale	3529	lime brkn 3852
lime brkn	3553	Total Depth.
shale	3560	
lime	3570	
sdv shale	3576	
br. lime & shale	3597	

Top Arbuckle 3832