

15-23-14W
COPY

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS

COMPANY KATHOL PETROLEUM INC

SEC. 15 T. 23 R. 14W

FARM Copeland

NO. 1

LOC. W $\frac{1}{2}$ NW NW

COUNTY Stafford

TOTAL DEPTH 4055'

COMM. 4-4-67

COMP. 4-14-67

SHOT OR TREATED

CONTRACTOR Kathol Pet. Inc.

ISSUED 9-9-67

CASING

20

10

15

8 5/8" 250' cem w/ 225 sx

12

6

13

5

ELEVATION 1950' KB

PRODUCTION 23 BOPD, NW

SIMP 3966-68

0	85	Sand
85	250	Shale - Red Bed
250	310	Shale - Red Bed
310	375	Sand
375	848	Red Bed
848	873	Anhydrite
873	1350	Shale - Shells
1350	1925	Shale & Shells
1925	2168	Lime & Shale
2168	2395	Lime & Shale
2395	2608	Lime & Shale
2608	2925	Lime & Shale
2925	3123	Lime - Shale
3123	3237	Lime & Shale
3237	3370	Lime & Shale
3370	3475	Lime & Shale
3475	3542	Shale
3542	3580	Lime
3580	3670	Lime
3670	3770	Lime
3770	3810	Lime
3810	3850	Lime
3850	3913	Lime-Shale-Chert
3913	3935	Cherty Lime
3935	3967	Cherty Lime
3967	3975	Sand
3975	3979	Sand
3979	3995	Sand - Lime
3995	4008	Lime - Shale
4008	4015	Lime
4015	4030	Lime
4030	4055	Lime

Set 250' of 8-5/8" surf.
casing with 225 sacks cement,
1% Gel.

TOPS: (Electric Log)

Anhydrite (Sample)	848'
Heebner	3406'
Douglas	3442'
Brown Lime	3542'
Lansing-Kansas City	3558'
Base-Kansas City	3800'
Conglomerate	3862'
Conglomerate Chert	3892'
Viola	3914'
Simpson Shale	3953'
Simpson Sand	3964'
Arbuckle	4009'
LTD	4054'
RTD	4055'

I certify to the best of my knowledge and belief, the above represents a true and accurate driller's log record of the captioned well.

Don G. C. ...