
Company. SKELLY OIL COMPANY
Farm. Leo R. Galliart No. 1

SEC. 2 T. 23 R. 16W
NW NW NE
330' fr NL & 330' fr WL NE¼
2-23-16W

Total Depth. 4107'
County. Pawnee
Comm. 5-2-49 Comp. 5-29-49
Shot or Treated. Acid. W/250 gals. 4099-4107' 5-30-49 by Dowell Inc.
Contractor. Claude Wentworth Drlg. Co., Inc.
Issued. 8-13-49

KANSAS



CASING:
8-5/8" 990' Cem. W/500 Sx.
5-1/2" 4099' Cem. W/150 Sx.

Elevation. 2020 Gnd

Production. before acid 350' OIH. after acid: flowed 8 hr. 37 BO, 16 BW to est. 24 hr. SCC Pot. 111 bbls.

Figures Indicate Bottom of Formations.

surface soil, clay & sand	150
shale & shells	340
shale, shells & red bed	455
sand	520
red bed & shalls	850
red bed, pyrites, sand & shells	985
anhydrite	990
anhydrite	1015
red bed & shale	1500
shale &lime shells	1875
lime	2120
shale & shells	2130
lime & shale	2180
shale	2200
lime	2520
lime & shale	3045
lime	3085
lime brkn	3205
lime & shale	3305
lime	3475
lime & shale	3610
lime	3974
redbed & shale	4000
lime & chert	4035
lime & shale	4060
shale & lime	4098
buff xlyn dolo. RTD	4106
buff dolomite	4107
Total Depth	

4098'-4106' slight por. & sat.
4106'-4107' good por. & oil stain.

Prod. Formation:
Arb. Lime 4099'-4107'

Tops:

Anhydrite	985
Heebner Shale	3489
Dodge Lime	3511
Douglas Sand	3526
Lansing Lime	3617
Conglomerate	3955
Simpson Shale	4040
Arbuckle Lime	4098