State Geological Survey
WICHITA, BRANCH

2-23S-22W

W E L L L O G

Well Name: # 2 Housman

Spud Date: 10-14-80

Completion Date: 10-23-80

Location: E SE SW Section 2-23S-22W
Hodgeman County, Kansas

Operator: Wheatland Oil & Gas, Inc.

Contractor: Ramco Drilling Corp.

Casing: 8 5/8" 28# used w/ 425 sx. psomis, 3% gel, 2% CaCl. 4½' w/225 sx.

FORMATION	FROM	TO
Surface Soils	0	704
Red Bed & Shells	704	1330
Anyhidrite	1330	1576
Red Bed & Shale	1576	2190
Shale & Shells	2190	2356
Red Bed, Shale & Lime	2356	2575
Shale	2575	2710
Shale & Shells	2710	2880
Lime, Shale & Shells	2880	3075
Shale & Shells	3075	4012
Lime & Shale	4012	4119
Shale & Lime	4119	4322
Lime & Shale	4332	4461
Rotary Total Depth		4461

2-23-22w
P(

D. BIRD OIL, INC.
LEIGH RAYMOND · STACY RAYMOND
P.O. BOX 255
BALDWIN CITY, KANSAS 66006
913 594-3982

RECEIVED
STATE CORPORATION COMMISSION
MAY - 6 1982
CONSERVATION DIVISION
Wichita, Kansas

State Geological Survey
WICHITA, BRANCH

October 31, 1980

Enclosed is data pertinent to the #2 Housman, drilled by Wheatland Oil & Gas, Inc.

#2 HOUSMAN (Elev: KB +2208)

NE/4, SE/4, SW/4 of Sec. 2-23S-22W, Hodgeman County, Kansas, commenced 10-14-80, completed 10-21-80. Rotary total depth was 4461'.

Structural relationships of the #2 Housman to nearby wells.

Wheatland Oil & Gas, Inc.

#2 Housman (SW/SE/SW Sec. 2-23S-22W)	Mid-Con Energy Corp. #1 Chilson (C-SWNW) IP 25BOPD	Wheatland Oil & Gas, Inc. (NE/SE/SW 2-23S-22W) IP120BPD
Lansing K.C. -1625'	-1642 (17' high)	-1625 (Flat)
Marmaton -2003'	-2010 (7' high)	-2005 (2' high)
Ft. Scott -2160'	-2172 (12' high)	-2159 (1' low)
Mississippian -2235'	-2246 (11' high)	-2232 (3' low)
Miss. Os. -2244'		-2243 (1' low)