

25076

SIDE TWO

Operator Name Hadson Petroleum Corporation Lease Name Sherman Well # 2-11

Sec. 11 Twp. 23S Rge. 31 East West County Finney

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken [X] Yes [] No
Samples Sent to Geological Survey [X] Yes [] No
Cores Taken [] Yes [X] No

Formation Description
[X] Log [] Sample

DST #1-2687-2702', 30/60/90/180 - 1st open FTP 230/287, SIP 595, 2nd open FTP 241/341, SIP 549, Recovered 679' of muddy salt water.
DST #2-4768-4780' - 30/60/90/180 - 1st open FTP 98/553, SIP 1279, 2nd open FTP 567/1068, SIP 1275, Recovered 35' of oil & 2292' of muddy water - Total recovery of 2327'

Table with 3 columns: Name, Top, Bottom. Rows include Krider, Heebner, Toronto, Lansing-Kansas City, Stark, Base/Kansas City, Pawnee, Ft. Scott, Cherokee, Morrow, St. Genevieve, St. Louis.

CASING RECORD [X] New [] Used
Report all strings set-conductor, surface, intermediate, production, etc.

Table with 8 columns: Purpose of String, Size Hole Drilled, Size Casing Set (in O.D.), Weight Lbs/Ft., Setting Depth, Type of Cement, #Sacks Used, Type and Percent Additives. Row 1: Surface, 12-1/4", 8-5/8", 20#, 430, Class H, 250, 2% CC.

PERFORATION RECORD and Acid, Fracture, Shot, Cement Squeeze Record. Columns include Shots Per Foot, Specify Footage of Each Interval Perforated, (Amount and Kind of Material Used), Depth.