WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

22-23-6W


Company. CITIES SERVICE OIL
Farm. Hamilton No. 1 SWD

SEC. 22 T. 23 R. 6W
NW SW SW SW
418' N & 272' E of SW cor.

Total Depth. 4735'
Comm. 8-24-58 Comp. 9-20-58
Shot or Treated.
Contractor. Barbour Drlg.
Issued. 5-2-59

County Reno

KANSAS



Elevation. 1555' Gr.

Production. S. W. D. W.

CASING:

10 3/4" 320' cem w/320 sx.
7" 4128' cem w/150 sx.
DV Tool 1218' cem w/951 sx.

Figures Indicate Bottom of Formations.

clay	25
sand	98
shale & shells	485
shells, lime & salt	875
lime & shale	1280
lime	1755
lime & shale	1920
lime	2000
shale & lime	2125
lime & shale	2360
lime	3410
lime & shale	3573
shale, lime & chert	3648
chert & lime	3735
cherty lime & shale	3800
lime & shale	3880
shale & lime	3907
lime & shale	4010
lime	4045
sand & lime	4078
lime	4080
lime, chert & shale	4105
Conglomerate	4117
lime	4155
cherty lime	4195
lime	4212
cherty lime	4295
lime	4324
chert & lime	4357
lime	4488
chert & lime	4521
lime	4574
lime & shale	4590
lime	4735
Total Depth	

DST 4111-25', op 1 hr, rec. 3300' salt water.

9-25-58 Acidized 6000 gals.
Input 632 bbls. per hr through casing.
Input through 4" tubing, 420 bbls. per hour.

TOPS:

Heebner	2747
Lansing	2975
Mississippi	3594
Kinderhook	3752
Hunton	3949
Viola	4006
Simpson Sand	4032
Arbuckle	4110
Rep	625