SIDE ONE

-		AFFIDAVIT	OF	COMPL
X	• •			

Two (2) copies o	f this form shall	be filed with the Ka	ansas Corporation Com-
			2, within thirty (30)
days after the comple	tion of a well, re	gardless of how the	well was completed.

Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on Side One will be of public record and Side Two will then be held confidential.

Applications must be made on dual completion, commingling, salt water disposal,

injection and temporarily abandoned wells.

X Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238.

LICENSE # 5087	EXPIRATION DATE	6-30-8	33	
OPERATOR <u>Texas Energies, Inc.</u>		API NO.	15-185-21,648	
ADDRESS P.O. Box 947	ÇÎ,	COUNTY_	Stafford	
Pratt, KS 67124		FIELD Ra	attlesnake Eas	<u>:t :</u>
** CONTACT PERSON E. H. Bittner	ar a	PROD. FO	RMATION	
PHONE (316) 672-751				
PURCHASER N/A	<u>C </u>	LEASE Ri	ixon	
ADDRESS		WELL NO.	1-18	
		WELL LOCA	ATION C SE SW	NE
DRILLING Wheatstate Drilling		<u>2310</u> Ft.	from North	Line and
CONTRACTOR ADDRESS		<u>1650</u> Ft.	from East	Line of
Pratt, KS 67124		the_ <u>NE/4</u> (Qtr.)SEC 18 TWE	24S RGE 13W.
PLUGGING Same As Above		Ī	WELL PLAT	(Office
CONTRACTOR				Use Only)
ADDRESS				KCC
	·			KGS
TOTAL DEPTH 4250 PE	TD			SWD/REP
PUD DATE 8-29-82 DATE COMPLETE	D 9-09-82		— 18 	PLG
ELEV: GR 1925 DF 1932 KB	1934			•
DRILLED WITH ((ABB) (ROTARY) (ATR)	TOOLS.	 		
DOCKET NO. OF DISPOSAL OR REPRESSURIN	G WELL BEING			
SED TO DISPOSE OF WATER FROM THIS LE	ASE			
Amount of surface pipe set and cement	ed <u>266</u> D	V Tool Us	sed? No	•
THIS AFFIDAVIT APPLIES TO: (Circle ON Injection, Temporarily Abandoned, OWW	E) - 0il, Gas, S O. Other	hut-in Ga	s, Dry, Dispo	sal,
ALL REQUIREMENTS OF THE STATUTES, RUL AND GAS INDUSTRY HAVE BEEN FULLY COMP	ES AND REGULATIO	NS PROMUL	GATED TO REGU	LATE THE OIL

AFFIDAVIT

E. H. Bittner that:	, being of lawful age, hereby certifies
I am the Affiant, and I am familiar was The statements and allegations contained t	with the contents of the foregoing Affidavit. therein are true and correct.
	E.H. Butu
	(Name)
SUBSCRIBED AND SWORN TO BEFORE ME thi	is 16th NeaBUr September
19_82.	TARV
	CATE! 12 #
	MOTO DV DUDI TO
MY COMMISSION EXPIRES: April 23, 1983	PUBLIC)
	—— *

** The person who can be reached by phone regarding any questions concerning this information.

SEP 21 box

OPERATOR Texas Energies, Inc. LEASE Rixon

SEC. 18 TWP. 24S RGE. 13W

	of norosity an	INFORMATI	of: cored inter	vels, and all di	ill-stem tests,		HOW GEOLOGICA	AL MARKER	S, LOGS R	UN, ON.
cluding depth interva	tested, cushion use	d, time tool op	in, flowing and	shut-in pressur	BOTTO	101.	HAME	<u> </u>	DEPTH	
FORMATIO	N DESCRIPTION, C	ONTENTS, ETC.		TOP	BOTTO		LOG TOPS Chase Towanda Ft. Riley Co. Grove Onaga Sh Wabaunsee Topeka Heebner Lansing B/KC Miss. Viola Simpson Arbuckle L.T.D.	2 2 2 2 2 3 3 3 3 4 4 4	1902 2029 2071 2252 2644 2706 3130 3449 3618 3878 3979 1070 1122 1188 1246	(-1 (-1 (-1 (-1 (-1 (-1 (-2 (-2) (-2 (-2 (-2 (-2)
DST #2 3936 DST #3 397 DST #4 4066 DST #5 412	FS1 3-3980 (Mi FS1 7-3994 (Mi . Oil 9-4096 (Vi 30 2-4152 (Si	IP 2038. iss.) 30 iP 105 iss.) 30 l; IFP 52 iola) Re 0-30-30-4 imp.Sd.)	0-45-45-6 0-30-30-3 2-52; ISI cc. 70' M 30-45-4 2 62-31;	tool 10" Rec. Rec. P 52; FF dd; IFP 5-60 Re	into se 70' Mud; 90' Slic P 104-10 72-72; 1 c. 65' S 9; FFP 6	econd IFP phtly 04; FS ISIP 7	105-105; 1 Gas Cut M IP 104 2; FFP 239 ly Gas Cut FSIP 727	ISIP 11 ud with 9-239;	l6; FF n a Tr FSIP	P 95 ace 312
	2-4002 (Mi Tot	iss.) tal Rec.	120' Sli	-30-30 ohtly Ga	FFP 45- s Cut ar	-45; F nd Oil	SIP 45 Spotted 1			
399 Report of all strin	2-4002 (Mi Tot	iss.) tal Rec.	120' Sli	-30-30 ohtly Ga	FFP 45- s Cut ar	-45; F nd Oil (New)	SIP 45 Spotted 1	X Type o	nd percen	
399	2-4002 (Mi Tot	iss.) tal Rec.	120' Sli	-30-30 ohtly Ga	FFP 45- s Cut ar	-45; F nd Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	ditives	_
399 Report of all strin	2-4002 (Mi Tot	iss.) tal Rec. intermediate,	120' Sli	-30-30 ohtly Ga	RECORD Type con	-45; F nd Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	and percent ditives	_
Report of all string	2-4002 (Mi Tot gs set — surface,	iss.) tal Rec. intermediate, Size casing set (in 0.D.)	120 Sli	-30-30 chtly Ga	RECORD Type con	-45; Find Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	ditives	_
Report of all string	2-4002 (Mi Tot gs set — surface,	iss.) tal Rec. intermediate, Size casing set (in 0.D.)	120 Sli	-30-30 chtly Ga	RECORD Type con	-45; Find Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	ditives	_
Report of all string	2-4002 (Mi Tot gs set — surface,	iss.) tal Rec. intermediate, Size casing set (in 0.D.)	120 Sli	-30-30 chtly Ga	RECORD Type con	-45; Find Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	ditives	_
Report of all string	2-4002 (Mi Tot gs set — surface,	iss.) tal Rec. intermediate, Size casing set (in 0.D.)	120 Sli production, et Weight lbs/ft.	-30-30 chtly Ga	RECORD Type con	-45; Find Oil (New)	SIP 45 Spotted 1 or (\$\$\$\$40	Type o	ditives	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4 LINER RECO	iss.) tal Rec. intermediate, Size casing set (in 0.D.) 8 5/8	120 Sli production, et Weight lbs/ft. 24	-30-30 chtly Ga c. CASING Setting depth 266	RECORD Type cor Lite	(New)	SIP 45 Spotted I or (%%%) Secks 30 100	Type o ed	g Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4	iss.) tal Rec. intermediate, Size casing set (in 0.D.) 8 5/8	120 Sli production, et Weight lbs/ft. 24	-30-30 chtly Ga c. CASING Setting depth 266	RECORD Type con	(New)	SIP 45 Spotted I	Type o ed	ditives	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4 LINER RECO	iss.) tal Rec. intermediate, Size casing set (in 0.D.) 8 5/8	120 Sli production, et Weight lbs/ft. 24	-30-30 chtly Ga c. CASING Setting depth 266	RECORD Type cor Lite	(New)	SIP 45 Spotted I or (%%%) Secks 30 100	Type o ed	g Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI	iss.) tal Rec. intermediate, Size casing set (in 0.D.) 8 5/8	120 Sli production, et Weight lbs/ft. 24	-30-30 chtly Ga c. CASING Setting depth 266	RECORD Type cor Lite	(New)	SIP 45 Spotted I or (%%%) Secks 30 100	Type o ed	g Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettom, ft. TUBING RECO	intermediate, Size casing set (in 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight Ibs/ft. 24	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (%%%) Secks 30 100	Type o ed	g Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (In 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (\$\$564) Secks 30 100 ATION RECOR	Type e ed	ditives R Gel	_
Report of all strin Purposa of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (in 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (\$\$564) Secks 30 100 ATION RECOR	Type o ed	ditives R Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (In 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (\$\$564) Secks 30 100 ATION RECOR	Type e ed	ditives R Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (In 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (\$\$564) Secks 30 100 ATION RECOR	Type e ed	ditives R Gel	_
Report of all strin Purpose of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (In 0.D.) 8 5/8 RD Secks c	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Gar c. CASING Setting depth 266	FFP 45-s Cut ar RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (\$\$564) Secks 30 100 ATION RECOR	Type e ed	ditives R Gel	_
Report of all strin Purposa of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECO	intermediate, Size casing set (in 0.D.) 8 5/8 RD Secks coord Packer ACID, FRACT	120 Sli production, et Weight lbs/ft. 24 ement	-30-30 chtly Garce. CASING Setting depth 266	RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted II Or (XXXXIII O) Or (XXXXIII O) Or (XXXIII O) Or (XXXIIII O) Or (X	Type e ed	ditives R Gel	_
Report of all strin Purpose of string Surface Purpose of string Surface N/A N/A	2-4002 (Mi Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bettem, ft. TUBING RECCI Setting depth	intermediate, Size casing set (in 0.D.) 8 5/8 RD Secks coord Packer ACID, FRACT	production, et Weight lbs/ft. 24 ement FURE, SHOT, material used	-30-30 chtly Garce. CASING Setting depth 266	RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (XXXXIII) Secks 30 100 ATION RECOR	Type e ed	ditives R Gel	_
Report of all strin Purposa of string Surface	2-4002 (Mi Tot Tot gs set — surface, Size hole drilled 12 1/4 LINER RECOI Bottom, ft. TUBING RECCI Setting depth Amo	intermediate, Size casing set (in 0.D.) 8 5/8 RD Secks c ORD Pecker ACID, FRACT unt and kind of	production, et Weight lbs/ft. 24 ement TURE, SHOT, moteriel used	-30-30 chtly Garce. CASING Setting depth 266	RECORD Type cer Lite Co	(New) nent PERFOR	SIP 45 Spotted I or (XXXXIII) Secks 30 100 ATION RECOR	Type e ed	ditives 28 Gel h interval	_