

STANOLIND OIL & GAS CO.
E. Van Lieu "B" No. 1.

SEC. 20 T. 24 R. 13 W
NE 1/4 SE
2310' N SL 2310' E WL SE 1/4

Total Depth. 4169'

Comm. 6-7-43 Comp. 6-28-43

Shot or Treated.

Contractor.

Issued. 8-7-43 Rotary O-4169

County. Stafford



CASING:
8 5/8"

276' 2" Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

cellar	6' 1"
sand	120
sand & shale strks	150
shale & shells	295
shale blue	305
red bed	403
sand & shale	470
lime	485
sand & shale	620
shale & shells	795
anhydrite	1011
shale & shells	1290
salt shells	1404
shale & shells	1427
sand & shale	1650
shale & lime, brkn	1700
lime	1725
lime brkn	1840
lime	1905
shale & shells	1970
lime	2020
lime & shale	2080
lime sdy	2150
lime & shale strks	2210
shale	2315
lime & shale	2556
shale & lime shells	2725
lime & shale	2894
shale blk & lime	2910
shale & lime	3220
lime	3240
lime sdy	3285
lime brkn & shale	3350
lime sft sdy	3395
lime	3515
shale & lime	3545
shale blk	3640
lime brkn	3705
lime hd	3710
lime & shale, brkn	3755
lime sdy & shale	3850
lime hd	3875
lime	3902
shale & chert	3946
shale	3973
lime	4018
lime & chert	4082
lime	4106
shale	4158
Arbuckle lime	4161
dolomite	4169
Total Depth.	

Tops: Lansing	3595
Viola Lime	4030
Simpson	4106
Arbuckle	4156- 4169