


36-24-13W

CONTINENTAL OIL CO.
G.W. James No. 1

SEC. 36 T. 24 R. 13 W
SEc SW
330' N 330' W of S $\frac{1}{4}$ Cor.

Total Depth. 4234'
Comm. 2-26-43 Comp. 3-19-43
Shot or Treated.
Contractor.
Issued. 4-17-43

County. Stafford



CASING:
10 $\frac{3}{4}$ " 280' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface clay	0-120
shale & shells	290
red bed & shale	715
anhydrite	745
shale & shells	750
sand & shale	1095
shale & shells	1115
salt & shells	1215
shale & shells	1590
sand & shale	1715
lime & sand	2025
lime & shale	2300
shale & shells	2405
lime & shale	2500
brkn lime & shale	2690
lime brkn	2995
lime & shale	3020
lime	3365
lime & shale	3615
lime	3945
sand & chert	4118
lime	4155
lime & shale	4165
lime	4234
Total Depth.	

Tops:	
Anhydrite	715
Topeka Lime	3000
Lansing Lime	3592
Viola Lime	4007
Simpson Sand	4115
Arbuckle Lime	4179

Cored 4183-96 rec. 9' of core-
no sh oil
Deepened to 4234-no sh oil-
conditioned hole to plug
Total Depth 4234 in Arbuckle
lime

Note: All above footages
are calculated from the
ground level