


10-25-14W

LION OIL REFG. CO.
Toland No. 1.

SEC. 10 T. 25 R. 14 W
C1W SE

Total Depth. 4464'
Comm. 4-3-43 Comp. 4-27-43
Shot or Treated.
Contractor. R.W. Rine Drlg. Co.
Issued. 5-15-43

County. Stafford



CASING:
8 5/8"

330' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

shale & sand	240
red bed	830
anhydrite	910
red beds & shale	1490
shale	1510
shale & sdy lime	1775
lime & shale	1950
lime	2040
shale	2080
sdv lime	2130
lime	2290
shale & lime	2365
shale	2777
lime	2810
shale	2900
shale & lime	2990
shale	3075
lime & shale	3300
lime	3340
lime & shale	3438
lime	3485
lime & shale	3628
shale	3690
lime	4035
lime & chert	4062
chert	4069
lime & shale	4102
shale	4122
lime & shale	4151
lime & chert	4197
chert	4277
shale	4305
lime & shale	4345
lime & chert	4374
lime	4464
Total Depth.	

Halliburton Drill Stem

Test at 3853

Drill pipe stuck-no test

98
43
153

Tops:
Lansing Lime 3679
Mississippi Lime 4034
Vicksburg Lime 4143
Simpson Sand 4296
Buckley Lime 4359