

16-25-14W
County. Stafford

Total Depth. 3828'
Comm. 10-27-40 Comp. 11-13-40
Shot or Treated. 11-16-40 5000 Gals. Acid
Contractor. Hissom Drlg. Co.
Issued. 12-21-40

Plotted
E.G.C.

CASING:
10 $\frac{3}{8}$ " 341'
5 $\frac{1}{8}$ " 3805'

Elevation.

Production. Pot. 17,849 B.
no wtr

Figures Indicate Bottom of Formations.

surface	38
wtr sand	150
shale & shells	341
red bed, shale, sand shells	703
shale	835
anhydrite	865
shale	935
shale & shells	1329
shale	1400
salt & shale	1660
shale	1760
lime	1824
shale & lime	1943
brkn lime & shale	2178
lime brkn	2255
brkn lime & shale	2345
shale & shells	2457
brkn lime & shale	2544
brkn sand	2562
shale	2565
lime brkn	2625
shale & lime	2764
brkn lime & shale	2865
shale & lime	2925
lime & shale brkn	2980
lime	3002
shale	3015
brkn lime & shale	3079
shale & lime	3195
lime	3369
lime & ohort	3385
lime hrd	3400
lime & shale	3515
lime	3532
brkn lime & shale	3590
lime	3620
shale	3641
lime	3769
cored lime (rec 9')	3779
lime (Top Pay 3799)	3800
rotary T.D. 3800=3806 SLM	
lime	3806-3828
Total Depth.	

Corr. Top Lansing 3647
Penetration 181

Pay 3813-3828