
24-25-15W

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- NADEL & GUSSMAN_ WESTERN PETROLEUM CO. SEC. 24 T. 25 R. 15W
Farm- Stambaugh No. 1 C SW SW

Total Depth. 4535'
Comm. 1-28-64 Comp. 2-12-64
Shot or Treated.
Contractor. Western Petroleum INC.
Issued. 5-9-64

County Stafford
KANSAS



Elevation. 1999' DF

Production. 169 BOPD

CASING:

8 5/8" 268' cem w/ 260 sx
5½" 4520' cem w/ 150 sx

Figures Indicate Bottom of Formations.

clay & sand	280
shale, red bed	710
red bed	935
anhydrite	960
shale shell	1835
lime & shale	1910
shale & lime	2110
lime & shale	3600
lime	3688
lime & shale	3780
lime	4036
lime & shale	4096
lime	4148
lime & shale	4241
chert, lime	4256
lime, shale, chert	4293
shale & chert	4346
chert & shale	4395
chert & lime	4426
chert, lime, shale	4465
chert & sand lime	4500
lime & shale	4535 RTD
Total Depth	

TOPS: LOG

Anhydrite	938
Heebner	3634
Toronto	3653
Lansing	3804
Base Kansas City	4082
Mississippian	4228
Kinderhook	4289
Viola	4336
Simpson	4455
Arbuckle	4506

DST #1 3935-3972' Op 1 hr. good blow for 1 hr. GTS in 29 min. Rec. 420' muddy oil as follows: 60' HOCM, 120' HO&GC Froggy Oil, 30' clean oil, 90' muddy oil, 30' CO, 90' Mo. IDIP 1410# 30 min., FSIP 1385# 30 min.. IFP 30#. FFP 145#.

DST # 2 4231-4245' 14' anchor. Op 1½ hrs. Good blow throughout test. GTS in 24min. TSTM. 75' GCM, NSof oil. IBHP 1060# 30 min.

DST #3 4245-4256' Op 2 hrs. GTS in 75 min. Fair blow thoroughout test. 25' GCM w/few specks of oil. IBHP 610# 30 min., FBHP 1350# 30 min., FP 0#, HH 2270#.

DST #4 4252-4278' GTS in 9min. Decreasing too fast to gauge. Flowed oil in 47min. Reverse circulating oil out of pipe. ISIP 1390# 30 min, FSIP 1405# 30 min, IFP 695#, FFP 1335#.