

Operator Name BEREXCO INC. Lease Name MARY RAYMOND Well# 1-16 SEC. 16 TWP. 25S RGE. 32W East West

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken Yes No
 Samples Sent to Geological Survey Yes No
 Cores Taken Yes No

Formation Description
 Log Sample

DST #1) 4788-4830
 Packer Failure

DST #2) 4753-4830 (Morrow Sd)
 30-60-30-90
 1st: Wk blow decr to very wk
 2nd: no blow
 Rec: 30' mud
 325/374 97/81 97/81

DST #3) 4825-4877 (St Louis)
 30-60-30-90
 1st: Wk blow died 20 min
 2nd: Wk blow died 10 min
 Rec: 50' oil spotted mud
 700/211 65/48 65/65 BHT 118°

CONFIDENTIAL

Name	Top	Bottom
Heebner	3912(-1023)	
Lansing	3997(-1108)	
Kansas C	4183(-1294)	
Marmaton	4430(-1541)	
Cherokee	4611(-1722)	
Morrow	4764(-1875)	
St Genieve	4803(-1914)	
St Louis "B"	4842(-1953)	
St Louis "C"	4926(-2037)	

CASING RECORD <input type="checkbox"/> new <input type="checkbox"/> used							
Report all strings set - conductor, surface, intermediate, production, etc.							
Purpose of string	size hole drilled	size casing set (in O.D.)	weight lbs/ft.	setting depth	type of cement	# sacks used	type and percent additives
Surface	12-1/4"	8-5/8"	24#	1915'	Lite	700	# Flo-Seal 3% CC
PERFORATION RECORD				Acid, Fracture, Shot, Cement Squeeze Record			
shots per foot	specify footage of each interval perforated			(amount and kind of material used)			Depth