

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY

503 East Murdock,


Wichita, Kansas

Company- STANOLIND OIL & GAS CO.  
Farm- Mason Gas Unit No. 1

SEC. 29 T. 25 R. 37W  
NE NE SW NE  
1000' N. of SL 1000' E. of WL NE  $\frac{1}{2}$

Total Depth. 2567  
Comm. 5-25-52 Comp. 6-19-52  
Shot or Treated.  
Contractor.  
Issued. 7-26-52

County Kearny KANSAS



CASING:  
8 5/8" 543' cem. w/400 sx  
5 1/2" 2542' cen. w/250 sx

Elevation. 3085  
3088 (land).  
Production. 13,413,000 Gas

Figures indicate Bottom of Formations.

surface sand	40
sand, gravel	90
yellow clay, shale	260
clay, shale	510
red bed	800
shale gyp	1450
gyp, anhy.	1629
gyp, anhy. shale	1830
anhy, shale	2135
lime	2505
lime, dolo.	2567
Total Depth	

Tops:  
Herington-Krider 2382  
Winfield 2444  
Towanda 2492  
Ft. Riley 2542

Ran 1 1/4" tubing set @ 2549'  
Schlumberger ran Gamma Ray  
and Micro Logs.

Lane wells perforated w/6  
shots per ft. as follows:

Herington-Krider, 2382-85',  
2387-90', 2398-2403', 2406-11',  
2414-23', 2434-39'.  
Winfield, 2444-50', 2455-62',  
2468-70', 2473-81'.

Towanda 2492-98', 2501-08',  
2510-13', 2515-19', 2523-27'.

Halliburton acidized as follows:  
Ft. Riley 2500 gals. 15%  
Herington-Krider 2500 gals. 15%  
Winfield 3000 gals. 15%  
Towanda 2500 gals. 15%  
All Zones 24000 gals. 7 1/2%