

5-25-40W

COMPANY PHILLIPS PET. CO.


SEC. 5 T. 25 R. 40W
 LOC. C NW SE

FARM Herndon "K" NO. 1

TOTAL DEPTH 2543'
 COMM. 7-23-65 COMP. 9-30-65
 SHOT OR TREATED
 CONTRACTOR E.F. Wakefield
 ISSUED 7-30-66

COUNTY Hamilton

KANSAS



CASING
 20 10
 15 8 5/8 506.89' w/210 sc em.
 12 6x 2 7/8 2029
 13 2 1/16 2019'

ELEVATION 3350' K.B.

PRODUCTION DRY

FIGURES INDICATE BOTTOM OF FORMATIONS

Sand	500	700
Sandy Shale	700	900
Anhydrite & Shale	900	1060
Sand & Shale	1060	1245
Anhydrite	1245	1270
Shale	1270	1320
Shale & Anhy. Streaks	1320	1655
Sand, Shale & Anhy.	1655	1770
Sand & Shale Streaks	1770	1880
Red Shale	1880	1910
Sand	1910	1940
Shale	1940	1970
Anhy. & Dolomite	1970	1995
Sand	1995	2005
Shale	2005	2030
Sand	2030	2040
Shale	2040	2230
Sand	2230	2245
Shale	2245	2255
Sand	2255	2260
Shale & Anhy. Streaks	2260	2455
Dolomite	2455	2460
Sand, Dolomite & Shale	2460	2543
RTD		2543

Set 2 7/8" Tbg. at 2029'; Second String 2 7/8" Tbg at 2019,
 With 111 sx.

Well P&A 9-30-65.
 Spudded 7-23-65.
 Ran Schlumberger

TOPS: SCOUT
 Cedar Hill
 Harper
 Cimarron
 B/Stone Corral
 Herrington
 Krider
 Winfield

SAMPLE
 1650
 1758
 1910
 1997
 2425
 2465
 2510