


GEO. E. REEVES
Stark No. 2.

SEC. 18 T. 26 R. 11 W
CNE NW

Total Depth. 4154'
Comm. 8-2-43 Comp. 9-15-43
Shot or Treated.
Contractor. Sharon Drlg. Co., Inc.
Issued. 10-23-43

County. Pratt



CASING:
8 5/8" 319' Cem.
5 1/2" 4146' Cem.

Elevation.

Production. Pot. 5903 B.
Deptho.

Figures Indicate Bottom of Formations.

	0-11	Geological Tops:
surface dirt		
sand & clay	40	K.C. Lime 3612 DF
sand	165	Viola 4145 DF
red bed	600	
red bed & shale	1015	
red rock	1050	
shale & shells	1230	
salt & shale	1380	
lime	1490	
shale	1595	
lime & shale	1700	
lime & sand	1730	
lime	1890	
lime brkn	1935	
lime	2175	
shale	2185	
lime	2200	
shale & lime strks	2299	
shale	2430	
lime	2445	
shale	2465	
lime brkn	2530	
shale	2815	
lime brkn	2870	
shale & shells	2975	
shale	3120	
lime	3150	
lime & shale	3220	
lime sft	3300	
lime	3394	
lime & shale	3520	
shale & sand	3552	
shale & shells	3584	
shale	3598	
shale & lime	3688	
lime	3921	
lime & shale	3994	
lime & chert	4004	
chert & shale	4039	
shale	4146	
lime & chert	4151	
4151 equals 4149		
lime	4154	
Total Depth.		