WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas.

13-26-12W

CITIES SERVICE OIL
Delaney No. 1.

SEC. 13 T. 26 R. 12W
CSL NE
1328.5' W 335' N of E/4

Total Depth. 4370'
Comm. 2-8-38 Comp. 3-15-38
Shot or Treated.
Contractor. Corbett & Barbour
Issued. 4-2-38

APR 2 1938

County. Pratt



CASING:
12½" 346'
7 " none run.

Elevation. 1866

Production. Dry

Figures Indicate Bottom of Formations.

sand	195	chert	4019	Schlumberger showed no oil 3-15-38	
shale & shells	453	shale	4026		
red rock & shells	715	shale & chert	4053		
red rock & shale	970	lime & shale	4067	Coring & Circulating	
shale & lime shells	1225	shale	4070	Sm sh oil 3653-55	
shells & salt	1335	chert	4072	cored 3655-65 (7' rec.)	
salt	1435	lime	4080	sh oil 3653-56	
shale & lime	1595	shale & lime	4139	Sm sh oil 3655-56	
brkn lime	1631	chert	4142	cored 3709-22 L.S.O.	
lime	1956	lime & shale	4157	cored 3742-52 no oil(9'rec)	
brkn lime	2058	chert & lime rough	4160	cored 3790-3800 very lgt stain	
lime shells & shale	2070	lime	4165		
shale	2080	chert rough	4170	3850' some sat., more than above.	
lime	2165	lime	4174		
brkn lime	2219	chert & lime	4175	cored 3995-4000 -no oil	
lime	2250	(stain 4175)		Circ. 4175-lgt stain	
brkn lime	2335	Viola lime	4184	cored 4179-84 very lgt stain.	
lime	2369	very lgt S.O. 4179-84			
brkn lime	2573	lime & chert	4198	cored 4317-32 lgt stain	
shale & lime shells	2655	chert & shale	4221	cored 4332-47 hrd, dry.	
shale	2698	lime, chert, shale	4237	best porosity 4347-52	
brkn lime	2745	chert & shale	4249	best porosity 4360-64	
shale & shells	2820	Simpson sand	4275		
shale	2840	shale, lime & shells	4297		
lime & shale	2970	shale & shells	4315		
shale	3005	lime	4317		
brkn lime	3103	lime cored	4322		
Topeka lime	3317	Arbuckle lime cored	4332		
lime	3340	Arbuckle lime	4337		
lime & shale	3356	Arbuckle lime cored	4347		
slate	3370	Arbuckle lime	4370		
Dodge lime	3490	Total Depth.			
lime	3548				
Dodge lime	3575				
shale	3615	Top Topoka 3105			
brkn K.C. lime	3625	Top Lans. - K.C. 3613			
sm sh oil 3653-3655		Top Eros. Miss. 3983			
K.C. lime	3720	Top Viola 4139			
sh oil 3709-3722		Top Simpson 4245			
cored 3655-65		Top Arbuckle 4316			
K.C. lime sft-lgt s.o.	-3723	Pen. 54			
K.C. lime hrd	3742	Total Depth 4370			
K.C. lime	3790				
cored 3742-52					
K.C. lime cored	3800				
stain 3790-3800					
K.C. lime sft	3870				
sh oil 3820-29					
K.C. lime & chert	3900				
K.C. lime	3940				
shale & lime	3960				
K.C. lime	3965				
brkn lime	3970				
shale	3983				
chert	3995				
chert & shale cored	4000				