

7-116 W-18 PERMANENT FILE COPY SEC. 28 TWP. 26S RGE. 34W

STATE Kans COUNTY Finney LOC. C SW NW

OPERATOR Helmerich & Payne, Inc. FT. FROM LIN

WELL NO. 1 FARM NAME Devlin Jones "C" FT. FROM LIN

POOL Pleasant Prairie ELEV. 2970E GR 2977 DF 2980 K

3/12/62 SPUD 3/6/62 COMP. 7/17/62

CONT. Sierra Rig #10 /GEOL.

NAME PRODUCING INTERVAL COMPLETION RECORD FROM - TO PERF. W/HOLES TREATMENT RECORD

a

b

c

d

a I. P. OIL/DIST. WTR. GAS M.C.F.P.D. CHK. HRS.

b " " " " " "

c "NOTE = This location was abd by Panhandle Dev. Co. On ..

d 11/6/61.

Temp. Abd. D & A (

SIP# FI TP # FI CPH SIBHP

GOR. GR. PBD TD 5189

SIZE DEPTH CASING - CEMENT RECORD SIZE DEPTH W/SAX.

8 5/8" @ 783 500

5" @ 5188 450

OPERATOR Helm. & Payne, Inc. WELL NO. 1 Devlin Jones "C" ELEV. 2980 KB

| SAMPLE TOPS | DEPTH | SUB SEA | ELEC. TOPS | DEPTH | SUB SEA |
|-------------|-------|---------|------------|-------|---------|
|-------------|-------|---------|------------|-------|---------|

|                  |  |  |    |      |     |
|------------------|--|--|----|------|-----|
| KB Tops & Datums |  |  | Hb | 3875 | 895 |
|------------------|--|--|----|------|-----|

|     |      |       |     |      |      |
|-----|------|-------|-----|------|------|
| RTD | 5189 | -2209 | Tor | 3890 | -910 |
|-----|------|-------|-----|------|------|

|  |  |  |      |      |      |
|--|--|--|------|------|------|
|  |  |  | Lans | 3923 | -943 |
|--|--|--|------|------|------|

|                   |  |  |     |      |       |
|-------------------|--|--|-----|------|-------|
| RTD 5189, Sj-Log. |  |  | BKC | 4482 | -1502 |
|-------------------|--|--|-----|------|-------|

|                     |  |  |      |      |       |
|---------------------|--|--|------|------|-------|
| 5" @ 5188 w/450 sx, |  |  | Marm | 4508 | -1528 |
|---------------------|--|--|------|------|-------|

|                          |  |  |       |      |       |
|--------------------------|--|--|-------|------|-------|
| Perf 16/5132-36 (St.Lou) |  |  | Chero | 4651 | -1671 |
|--------------------------|--|--|-------|------|-------|

|                        |  |  |       |      |       |
|------------------------|--|--|-------|------|-------|
| Acid, no take, Re-perf |  |  | Atoka | 4860 | -1880 |
|------------------------|--|--|-------|------|-------|

|                            |  |  |      |      |       |
|----------------------------|--|--|------|------|-------|
| 16/5132-36 (St L) 500 acid |  |  | Morr | 4920 | -1940 |
|----------------------------|--|--|------|------|-------|

|                      |  |  |         |      |       |
|----------------------|--|--|---------|------|-------|
| Swb 1d, Swb 4 GO & 4 |  |  | St. Gen | 4984 | -2004 |
|----------------------|--|--|---------|------|-------|

|                           |  |  |         |      |       |
|---------------------------|--|--|---------|------|-------|
| GWPH/NT. PB 5112, 6/5078- |  |  | St. Lou | 5073 | -2093 |
|---------------------------|--|--|---------|------|-------|

|                        |  |  |                |  |  |
|------------------------|--|--|----------------|--|--|
| 81, 18/5088-97, 1000A, |  |  | LTD (St.L)N.A. |  |  |
|------------------------|--|--|----------------|--|--|

no rec 1d, 500 A, CO 5150.

Frac (20,000 Gal Jell SW & 20,000# sd, Swb part Ld & Tr

oil. POP. P. 1d, Pump 9 BO & 1d/24 hours. P 3 BO & 17

BWPD. MICT TO RE-Work. CO 5115, 21/5018-25 (St Gen) PB

5050, 500 acid, (15%) SI/12hrs, FU 90' AW/scum oil,

24/4988-94 (St Gen) PB 5015, 5000 acid, 4988-94 (St Gen)

Rec all 1d, P 7-BO & 21 BW/24 hrs. P 7 BO & 22 BW/24 hrs.

Temp. Abd. 6/26/62.

COMPLETED

LIBERAL ELECTRIC LOG TOPS

2980 KB

Winfield 2590 (+390)

Heebner 3878 (-890)

Toronto 3888 (-900)

Lansing 3922 (-942)

Marmaton 4506 (-1520)

Morrow 4920 (-1940)

Ste. Gen 4982 (-2002)

St. Louis 5072 (-2092)

"B" Zone 5130 (-2150) 3' por

"C" Zone 5163 (-2183) 4' por

TD 5185