

5-26-37W

KANSAS WELL LOG BUREAU--- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

COMPANY STANOLIND OIL AND GAS COMPANY

FARM Otto Waechter "A" NO. 1


SEC. 5 T. 26 R. 37W

LOC. SW SW NE

200' N. of the S. line and 250' E. of the W. line of the NE 1/4

COUNTY Kearny

KANSAS



TOTAL DEPTH 2573  
 COMM. 11-25-50  
 SHOT OR TREATED  
 CONTRACTOR  
 ISSUED 2-10-51

COMP. 12-3-50

CASING

10 3/4" 565 cem. w/375 sx  
 7" 2530' cem. w/300 sx

ELEVATION 3084

*3087 Ind.*

PRODUCTION 31,000,000 gas

FIGURES INDICATE BOTTOM OF FORMATIONS

clay, sand 40  
 shale 60  
 blue shale, sand 450  
 sand 510  
 red bed 765  
 red rock, sand 1000  
 anhydrite 1030  
 red rock 1085  
 anhydrite, red bed 1800  
 salt, red rock 1880  
 anhydrite, red rock 1990  
 salt, anhydrite 2120  
 red rock 2200  
 anhydrite 2375  
 anhydrite, lime 2425  
 lime, shale 2550  
 lime 2573  
 Total Depth 2573

Herington-Krider w/2500 gal. 15%, flushed w/1800 gal. water.  
 All zones w/18,000 gal. 7 1/2%, flushed w/4400 gal. water.  
 All zones w/12,000 gal. 7 1/2%, flushed w/4400 gal. water.  
 All zones w/12,000 gal. 7 1/2%, flushed w/4400 gal. water.

Tops:

Herington-Krider 2600  
 Winfield 2665  
 Towanda 2712  
 Ft. Riley 2772  
 Schlumberger 2574

Lane Wells perforated w/6 SPF:

|           |      |      |
|-----------|------|------|
| Herington |      |      |
| Krider    | 2365 | 2377 |
|           | 2380 | 2386 |
|           | 2390 | 2396 |
| Winfield  | 2404 | 2415 |
|           | 2416 | 2427 |
|           | 2430 | 2438 |
| Towanda   | 2479 | 2509 |

Chemical Process acidized:

Ft. Riley w/2500 gal. 15%, flushed w/4400 gal. water.  
 Towanda w/3000 gal. 15%, flushed w/600 gal. water.  
 Winfield w/3000 gal. 15%, flushed w/600 gal. water.

4