


34-26-39W

WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company-Stanolind Oil & Gas Co.
Farm-R. B. Fegan "B" No. 1

SEC. 34 T. 26 R.39W
SW SW SW NE
150'N of SL 150'E of WL
NE 1/4
County Hamilton
KANSAS

Total Depth. 2585
Comm. 8/13/52 Comp.8/29/52
Shot or Treated. see record below
Contractor.
Issued. 10/11/52



CASING:
10 3/4" 586' cem w/400 sx
6" 2560' cem w/300 sx
1 1/2" tbg. 2581'

Elevation. 3251
3254 (2nd)
Production. 11,389,000 Gas

Figures indicate Bottom of Formations.

surface clay-sand gravel	200	Schlumberger ran Gamma Ray & Micro	
clay-shale	545	Logs.	
red bed	820		TOPS
red bed-gyp	1130		
gyp	1200	Herington-Krider	2383
gyp-shale-anhydrite	1520	Winfield	2443
anhydrite	1540	Towanda	2505
shale-anhydrite	2000	Ft. Riley	2560
anhydrite-lime-shale	2290		
lime	2405		
lime-dolomite	2585	T. D.	

McCullough perforated w/6 shots per ft. as follows:
Herington-Krider, 2387-2396, 2399-2406, 2413-2416, 2422-2426.
Winfield, 2443-2455, 2457-2461, 2468-2472, 2481-2483, 2495-2498.
Towada, 2505-2511, 2514-2418, 2520-2522, 2524-2533, 2537-2543.

Chemical Process acidized as follows:

Ft. Riley	2500 gals	15%
Herington-Krider	2500 gals	15%
Winfield	2000 gals	15%
towanda	3000 gals	15%
All zones	24000 gals	7 1/2%