

PL

MAGNOLIA PETROLEUM CORP.
 Amos Rodgers No. 1.


SEC. 9 T. 26 R. 4W.
 SW SE SW
 1020' FEL 330' fr SL SE SW

County. Reno.

Total Depth. 4042.
 Comm. 9-14-35 Comp. 11-16-35
 Shot or Treated.
 Contractor.
 Issued. 12-14-35.

CASING.

15 1/2" 142'
 9" 3622' SLM
 7" 4041'



Elevation. 1503

Production. 948 B. Pot.

Figures Indicate Bottom of Formations.

red rock	65	shale sand lime	3250
red rock and sand	142	lime	3388
lime and shale	327	lime and shale	3430
shale and shells	725	lime	3499
salt and shells	760	lime and shale	3587
lime and shale	880	shale and lime	3614
lime	930	chat	3617
salt	995	Standardized	
shale and shells	1235	chat	3693
lime	1265	limes.	3700
shale sticky	1277	lime	3920
lime	1335	shale	4005
shale and shells	1510	Misner sand	4006
lime	1530	Sylvan shale	4016
sticky shale	1555	lime	4025
lime and shale	1790	Sylvan shale	4040
lime	1918	Viola lime	4041
shale and lime	2274	lime OIL	4042
lime	2295	Total Depth.	
shale sticky	2305		
lime	2385		
shale	2391		
lime	2430		
shale and shells	2468		
lime soft	2552		
lime and shale	2600		
lime	2740		
broken lime sand	2750		
shale and shells	2818		
shale	2836		
lime hard	2840		
sdv shale soft	2850		
lime	3000		
shale	3025		
lime	3170		

4040
1503

2537