


SHELL PETRO. CORP.
F.L. Reece No. 5.

SEC. 11 T. 26 R. 9W.
SW SW SW
440' SL 440' WL SW $\frac{1}{4}$

County. Reno



Elevation.

Production. Pot. 3999 B.

Total Depth. 4140'
Comm. 2-26-37 Comp. 4-16-37
Shot or Treated. 2000 Gals.
Contractor. Olson Drlg. Co.
Issued. 5-15-37

CASING:
10 $\frac{3}{4}$ " 181'
7" 4133'

Figures Indicate Bottom of Formations.

clay & sand	65	lime med sft	3472
red rock	181	lime hrd	3510
red rock, shale & lime shells	280	lime sft	3514
shale & shells	515	lime hrd	3559
shale	1200	lime sft	3563
lime & shale	1473	lime hrd	3602
brkn lime	1549	lime	3689
lime & shale	1766	lime & shale	3764
SLC 1766-1735		lime brkn	3794
lime & shale	1791	lime & shale	3814
lime & shale	2113	shale	3841
shale	2253	shale	3870
lime & shale	2415	chat	3905
lime	2440	chert	3911
shale & lime	2458	lime & chert	3934
shale	2483	lime hrd	3944
lime	2505	shale	4054
brkn lime	2518	shale	4061
lime	2604	lime	4068
shale & lime	2645	shale	4126
lime	2688	lime hrd	4130
lime & shale	2949	shale	4132
shale	2989	Core #1	
sdv lime	3010	Cored 4132-4133 Rec. 10"	
lime	3114	Rec. 8" shale	4132 $\frac{3}{4}$
shale & lime shells	3181	Rec 2" conglomerate & dolomite	4133
brkn lime	3215	dolomite & chert	4134
lime	3227	Core #2	
Plugged back		Cored 4133-4137 Rec. 2 $\frac{1}{2}$ "	
cement	3227 -2626	Rec. 10" cement	4134
cement	2626-2666	Rec. 6" dolomite	4134 $\frac{1}{2}$
cement & shale	2666-2683	oil stained	
cement	2711	Rec. 4" chert & dolomite	4135
shale	2725	Rec. 10" dolomite	
cement	2858	well oil stained	4136
Plugged back 2549		dolomite	4137
cemont	2731	Core #3	
shale	2750	Cored 4137-4140 Rec. 1"	
shale & lime	2802	Rec. 1" dolomite	
shale	2840	oil stained	4138
shale	2870	Rec. 11" chert & dolomite	4140
lime	2882	Total Depth.	
lime & shale	2910		
shale & lime shells	2948		
lime & shale	3009		
shale	3024		
lime	3041		
lime hrd	3057		
shale	3066		
lime	3115		
shale	3127		
lime	3141		
lime	3206		
shale & brkn lime	3276		
brkn lime	3340		
lime hrd	3387		
lime med sft	3393		
lime hrd	3423		
lime hrd	3458		