

SHELL PETRO. CORP.
 Mary Whipple No. 8

Sec 15 T. 26 R. 9W.
 Cen NE $\frac{1}{4}$
 1319' fr EL 1308' fr SL 20'E &
 20'S of C.L.

Total Depth. 4139
 Comm. 5-4-37 Comp. 5-31-37
 Shot or Treated. 2000 gal.
 Contractor.
 Issued. 6-26-37

County. Reno.



CASING.

103/4" 307' 7" 4134'

Elevation.

Production. Pot. 2746 B.

Figures Indicate Bottom of Formations.

surface soil & sand.	103	lime and shale	3831
shale and shells	132	shale	3874
red bed and shale	221	chat	3912
shells	235	lime and chat	3919
red rock	307	lime & chert	3926
red sand rock	481	lime	3945
shale and shells	979	lime & shale	3955
shale	1130	shale	4133
lime	1144	4133 equals 4134 SLC	
shale and lime shells	1245	cored 4134-4136 Rec. 1 $\frac{1}{4}$ '	
salt	1272	Rec $\frac{1}{4}$ ' shale brownish blk 4134 $\frac{1}{2}$ '	
broken lime	1293	Rec 1' dolomite brown hard 4136	
lime and shale	1406	cored 4134-4139 Rec. 2 $\frac{1}{2}$ '	
broken lime	1476	Rec 1' cement	4136
lime and shale	1610	No rec. chert	4136 $\frac{1}{2}$ '
shale and shells	1680	Rec 1' dolomite and	
lime	1805	little chert	4138
red bed	1815	Rec $\frac{1}{2}$ ' dolomite	4139
lime and shale	1832	Total Depth.	
lime and shale	1904		
shale lime shells	2038		
shale and shells	2070		
shale and lime	2080		
shale and shells	2090		
lime and shale	2142		
shale and lime	2215		
shale	2250		
lime	2255		
shale and lime	2423		
shale and lime	2504		
broken lime	2590		
lime and shale	2738		
shale	2860		
lime and shale	2882		
lime and shale	2976		
broken lime	3018		
lime hard	3054		
broken lime	3141		
lime	3202		
broken lime	3344		
lime hard	3386		
lime med soft	3396		
lime hard	3462		
lime med soft	3477		
lime hard	3511		
lime soft	3516		
lime hard	3551		
lime med hard	3560		
lime med soft	3571		
lime med hard	3580		
lime	3681		