


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- SKELLY OIL COMPANY
Farm- Ruth Wyman No. 1

SEC.. 20 T. 26 R. 9W
NE SE SW
330' fr EL, 990' fr SL
of SW/4

Total Depth. 3923' PB 3917'
Comm. 5-2-59 Comp. 5-15-59
Shot or Treated.
Contractor. Claude Wentworth Drlg.
Issued. 8-29-59

County Reno KANSAS



Elevation. 1702' DF 1 \

Production. 9,009,000 CFG

CASING:

8 5/8" 430' cem w/250 sx.
5 1/2" 3923' cem w/150 sx.

Figures Indicate Bottom of Formations.

surface soil, sand & red bed	125
shale & red bed	580
shale, sand & clay	775
shale, sand & lime	896
shale and shells	1175
shale and lime	2407
shale and shells	2450
shale, shells and lime	2750
shale	3000
lime and shale	3450
lime	3903
partly tripolitic chert	3917
white to cream, partly tripolitic chert	3923
Total Depth	
Plugged back to 3917'	

TOPS:

Heebner Shale	3208
Brown Lime	3369
Lansing Lime	3401
Mississippi Lime	3903

DST #1 packer set @ 3904', used 13' anchor, op 1 hr, strong blow of air immediately, gas to surf. in 3 mins., gas gauged 489 MCF in 10 mins., rec. 150' gas cut mud, IBHP 1365# IFP 127#, FFP 127#, FBHP 1330#/20 mins.

Ran Schlumberger Survey.

Perf. #1 3905-3914' 54 holes.
Treatment #1 Acidized between 3905-3914' 5-21-59, using 250 gals. of acid & 94 barrels of oil.
Treatment #2 Sand-Acid Frac - 3905-3914' Used 3000# sand, 3000 gals. of gelled acid, 22 barrels of oil to flush.

Producing Formation: Mississippi Lime
Top 3905' Bottom 3914'