

Location SW SE SW SW
330' frm SL 825' frm WL SW/4

Sec. 2 T. 27 R. 1W

Casing Record

County- Sedgwick

10" 2018 Farm- J.W. Peachey No. 1
20" 63' 9" SLM 2699 Company- T.C. Johnson
15 1/2" 245 65/8" 3120 Contr.-
12 1/2" 1305 53/16" 3413 SLM Firm.- 10-11-29 Comr.-12-13-29
Total Depth 3519 Shot Quarts Between
Correspondence Regarding This Well Should Be Referred to



Figures Indicate Bottom of Formations.

Elevation Initial Production Dry & A.

Date Issued. 1-11-30

Formation	Depth	Formation	Depth	Formation	Depth
sand	50	lime 1/2 BW 1595'	1615	Show Oil 3108-3110	
shale blue	180	shale	1635	also 7 BW. HFW 3110-	
wtr sand	190	shale drk	1675	3120'.	
lime lgt HFW 190'	200	lime wh 1 BW 1680'	1730	lime sdy wh	3175
shale blue	205	shale	1765	More wtr 3140-3150'.	
slate	220	lime gray	1800	lime	3270
lime	235	shale blk	1805	red rock	3273
shale blue	250	lime wh	1820	lime wh	3305
lime lgt	275	shale lgt	1870	shale blue	3315
shale blue	285	lime	1895	lime gray	3330
lime	335	lime sdy	1940	shale blk	3378
shale	340	5 BW 1935-40'.		lime wh	3379
lime gray	415	lime	2050	*shale drk	3415
shale	425	HFW 1950-55'.		lime sdy	3418
lime lgt	468	shale drk blue	2055	Steel Line Correction	
red rock	473	lime 2 BW 2060'.	2075	Log is 3415 is 3413	
lime	520	shale blk	2095	SLM corrected.	
Show Gas 505'.		shale	2100	HFW 3415'.	
shale blue	525	lime	2125	sand	3440
lime lgt 1 BW	635	shale	2140	sand	3465
shale lgt	650	lime	2160	shale	3467
lime	730	shale drk blue	2210	sand	3504
shale blue	735	lime sdy	2220	HFW 3467-3470'.	
1 BW 720'.		shale 2 BW 2205'	2300	lime sdy hrd	3516
red rock	745	lime	2320	lime sdy sft	3519
lime gray	755	shale	2330	HFW 3416-3419'.	
shale drk	760	lime	2385		
lime	765	shale blue	2450	Total Depth	3519
shale blk	775	lime	2465		
lime	790	shale	2515	*Shale drk	3379-3415
shale blk	795	shale sdy blue	2595	Steel Line Correction	
lime lgt	825	shale wh	2615	3415 C.M. is 3413 SLM	
shale blue	830	lime	2660	Shale drk 3413 SLM	
lime	840	lime sdy 1 BW	2665	3415.	
shale	845	lime	2685	Top of Simpson	
lime	865	lime sdy	2705	Dolomite 3415'.	
shale blue	870	3 BW 2695'.			
lime	880	HFW 2700-2705'.		U.R. 8 1/4" 3065' and	
red rock	895	Steel Line Correction		3074'.	
shale	900	2705 is 2699 SLM		U.R. 6" 3180'.	
lime wh	930	lime sdy	2704	U.R. 5" 3467'.	
shale drk	940	lime	2717		
lime wh	975	shale blk	2727		
shale lgt blue 3BW	980	lime sdy	2735		
lime sdy	1040	Small Show Oil	2727-29'		
shale drk	1050	lime hrd	2752		
lime	1060	1 BW 2735-2740'.			
shale	1100	shale blk	2755		
lime	1105	lime	2790		
shale blue	1200	1 BW 2775-2780'.			
sand 2 BW 1220'	1230	shale drk	2885		
shale blue	1270	lime gray	2925		
lime	1275	shale	2960		
shale drk	1305	lime	2990		
lime sdy	1325	shale gray	3000		
shale drk	1375	lime	3020		
lime	1400	shale & shells	3045		
shale	1410	Varicolored shale	3065		
lime	1460	lime	3070		
shale drk blue	1475	shale	3085		
lime	1480	red rock & shale	3090		
shale blue	1485	Varicolored shale &			
lime 1 BW	1500	lime shells	3108		
shale drk blue	1560	chert	3120		