

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY  
 Union National Bk Bldg., Wichita, Kansas.

SKELLY OIL CO.  
 Interurban No. 2


SEC. 30 T. 27 R. 10W.  
 NE COR SW

Total Depth 3447'  
 Comm. 7-17-35 Comp. 9-5-35  
 Shot or Treated.  
 Contractor  
 Issued. 10-12-35

County- Pratt

CASING

12 1/2" 334  
 7" 3403



Elevation

Production Pot. 216 bbls.

Figures Indicate Bottom of Formations.

surface sand	60	Next 1' shelly lime gray shale	
red rock, shells & sand	90	Next 4" dark asphaltic shale	
red rock sand & shells	240	last 3' 8" dense grey, brown fossiliferous lime	
sand	250	last 1' saturated.	
red rock sand & shells	345	TOP LANSING	3402
red rock & shells shale & shells	375	lime dolomitic 3406-11	
shale, shells, salt & gyp	780	lime small amount	3418
salt & gyp	1080	lime brown	3421
salt gyp & shells	1280	lime gray	3428
shale lime & shells	1305	lime gray brown little shale	3434
shale & shells	1420	lime brown grey	3447
shale, lime & shells	1570	Total Depth	3447
shale lime & shells	1690	Gas Inc. 20,000	
lime	1735		
shale lime shells	1775		
lime	1970		
lime shells & shale	2065		
lime	2095		
shale, lime & shells	2325		
shale & shells	2390		
shale lime & shells	2705		
shale & lime	2785		
shale lime & shells	2905		
shale & lime	2980		
lime	3050		
shale & lime	3075		
lime	3136		
Correct SLM 3080 = 3075SLM			
shale & lime	3185		
lime	3390		
shale & lime	3394		
Cored 3394-3406			
Recovered 6 1/2'			
1st 1 1/2' shale drk			