

WELL LOG BUREAU KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company - DRILLERS GAS CO.
Farm - Fitzsimmons No. 4

SEC. 35 T. 27 R. 11 W
CN/2 NW SW

Total Depth. 3515' PB 3511½'
Comm. 4-24-46 Comp. 5-20-46
Shot or Treated.
Contractor. Thos. H. Allan
issued. 6-22-46

County. Pratt
KANSAS



CASING:

8 5/8" 403' Cem.
5½" 3498' Cem.

Elevation. _____

Production. Swab 46½ BO &
54½ Wtr. 3 hrs.

Figures Indicate Bottom of Formations.

soil & sand	0-40	shale	3300
sand & gravel	130	lime wh	3310
shale red & sand	180	shale sdy	3325
red beds	428	shale	3338
anhydrite sft wh	452	shale sft wh	
grit red	500	micaceous	3378
red beds	700	shale	3430
shale	900	pyritic shale	3456
salt & shale	1350	lime brwn	3465
anhydrite & shale	1590	shale	3476
anhydrite	1620	lime	3498
shale	1640	R. U. S. T.	
dolomite & lime	1670	lime wh	3500
dolomite cherty	1690	lime brwn	3502
lime & shale	1725	shale gy	3504
shale red	1742	lime gy	3508
dolomite cherty	1770	lime wh partly oil	
lime, part		saturated	3515
oolitic	1825	Total Depth PB 3511½'	
shale	1836		
lime cherty		Swbd 46½ BO & 54½ BW in	
fossiliferous	1875	3 hrs.	
shale & lime		Treated 5000 gal. acid (600# - 0#/39 mins.)	
shells	1975		
lime wh	1995	Tops:	
shale	2025	Anhydrite	428
lime	2085	Ft. Riley	1742
shale & lime		Base Florence	
shells	2135	Flint	1875
shale red	2145	Iatan	3456
lime	2190	Lansing	3476
lime & shale	2218		
lime sft oolitic			
faint oil			
stained	2262		
shale & lime			
shells	2740		
lime	2760		
shale	2810		
lime	2840		
shale	2860		
sand wh	2870		
shale	2900		
lime	2905		
shale	2910		
lime wh	2940		
cherty lime	2955		
shale drk	2970		
lime	3010		
shale & lime	3045		
lime wh	3170		
shale	3175		
lime	3205		
shale	3210		
lime	3250		
shale gy & blk	3275		