

22-27-244
115-184
HCC

TYPE B?

AFFIDAVIT OF COMPLETION FORM X

ACO-1 WELL HISTORY

Compt. _____

SIDE ONE

(Rules 82-3-130 and 82-3-107)

This form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ninety (90) days after the completion of a well, regardless of how the well was completed.

FOR INFORMATION REGARDING THE NUMBER OF COPIES TO BE FILED AND APPLICATIONS REQUIRING COPIES OF ACO-1 FORMS SEE PAGE TWO (2), SIDE TWO (2) OF THIS FORM.

FL Letter requesting confidentiality attached.

CW Attach ONE COPY of EACH wireline log run (i.e. electrical log, sonic log, gamma ray neutron log etc.)***Check here if NO logs were run _____.

PLEASE FILL IN ALL INFORMATION. IF NOT AVAILABLE, INDICATE. IF INFORMATION LATER BECOMES AVAILABLE, SUBMIT BY LETTER.

WELL # 5123 EXPIRATION DATE 6/85

OPERATOR Pickrell Drilling Co. API NO. 15-057-20,362

ADDRESS 110 N. Market, Suite 205, COUNTY Ford

Wichita, Kansas 67202 FIELD Wilroads

** CONTACT PERSON Jay McNeil PROD. FORMATION _____

PHONE 262-8427

PURCHASER _____ LEASE #3 Roenfeldt 'A'

ADDRESS _____ WELL NO. 3

WELL LOCATION NE SW SW

DRILLING Pickrell Drilling Company 990 Ft. from South Line and

CONTRACTOR ADDRESS 110 N. Market, Suite 205 990 Ft. from West Line of

Wichita, KS. 67202 the SW (Qtr.) SEC 22 TWP 27S RGE 24W (W).

PLUGGING Same WELL PLAT _____ (Office Use Only)

CONTRACTOR _____

ADDRESS _____

TOTAL DEPTH 5240' PBTD _____

SPUD DATE 12-23-83 DATE COMPLETED 1-5-84

EV: GR 2530 DF 2532 KB 2535

DRILLED WITH ~~(WIRELINE)~~ (ROTARY) ~~(WIRELINE)~~ TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE _____

Amount of surface pipe set and cemented 513' KB DV Tool Used? _____

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion _____. Other completion _____. NGPA filing _____.

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T

C.W. Sebitts

_____, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit.

WELL PLAT		(Office Use Only)
<div style="text-align: center;"> <p>22</p> <p>RELEASED</p> <p>Date: FEB 1985</p> <p>FROM CONFIDENTIAL</p> </div>		KCC _____
		KGS <input checked="" type="checkbox"/>
		SWD/REP _____
		PLG. _____

WPC - 22 - 22

ACO-1 WELL HISTORY

SIDE TWO , Pickrell Drlg. Co.
OPERATOR

LEASE NAME

#3 Roenfeldt 'A'

22-27S-24W

(E)

SEC.

TWP.

RGE.

(W)

FILL IN WELL LOG AS REQUIRED: WELL NO.

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Show Geological markers, Logs run, or Other Descriptive information.

Formation description, contents, etc.

Top

Bottom

Name

Depth

Check if no Drill Stem Tests Run.

Check if samples sent to Geological Survey.

DST #1 4868'-4900', 30"-60"-90"-90",
Rec. 60' SOCM, IFP 25#-33#, FFP 33#-59#, ISIP 482#, FSIP 549#.

DST #2 5026'-5072', 30"-60"-90"-90",
Gd blow, Rec. 15' mud, IFP 50#-50#,
FFP 50#-50#, ISIP 110#, FSIP 110#.

DST #3 5084'-5098', 30"-30"-30"-30",
Rec. 10' mud, IFP 25#-25#, FFP 25#-25#
ISIP 541#, FSIP 220#.

ELOG TOPS:

Heebner	4227(-1692)
Br Lm	4340(-1805)
Lansing	4350(-1815)
Stark	4676(-2141)
B/KC	4796(-2261)
B/Paw	4940(-2405)
Cherokee	4972(-2437)
B/I	5040(-2505)
Miss	5080(-2545)

If additional space is needed use Page 2,

Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
SURFACE	12 1/4	8 5/8"	20#	513' KB	60/40 poz	280	3%cc-2%gel

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval

TUBING RECORD

Size	Setting depth	Packer set at