

WELL LOG BUREAU KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas


Company . CITIES SERVICE OIL CO. et al
Farm Jones "C" No. 1.

SEC. 3 T. 28 R. 34W
CE/2 NE SW
660' S, 100' W of Cen.

Total Depth. 2865'
Comm. 11-7-45 Comp. 11-15-45
Shot or Treated. 13,000 gals. 15%, 4000 gals. 7 1/2%
Contractor. Baco Drilling Co.
issued. 3-2-46

County. Haskell

KANSAS



Elevation. 3076 ft

CASING:
8 5/8" 812' Cem.
5 1/2" 2865' Cem.

Figures Indicate Bottom of Formations.

Production. 20 min. O. F.
34,300,000 cu.ft. Gas
S.I.P. 434.5#

| | |
|-------------------|-------|
| clay & sand | 0-590 |
| clay | 750 |
| red rock | 1280 |
| red rock & sand | 1860 |
| red bed | 1955 |
| lime & shale | 2275 |
| red bed & shale | 2345 |
| anhydrite & shale | 2525 |
| anhydrite & lime | 2575 |
| lime & shale | 2725 |
| lime | 2865 |
| Total Depth | |

Electric Log

Drilled Cement to 2826 S.L.M.

Perforated:

| | |
|---------------------|-----------|
| 89 shots 2774-2810, | 1,800 MCF |
| 20 shots 2804-2810, | 2,600 MCF |
| 76 shots 2678-2700, | 3,410 MCF |
| 37 shots 2730-2742, | 3,650 MCF |

Acid Record:

| |
|---------------------------|
| 500 gals. to clean perms. |
| 700 gals. 2774-2810 |
| 800 gals. 2768-2742 |
| 1000 gals. 2678-2700 |
| 10000 gals. in all zones |
| 4000 gals. 7 1/2% acid in |
| all zones. |