
Company- THE TEXAS COMPANY
Farm- J. W. Combs No. 1

SEC. 26 T. 29 R. 13W
NW NW SE
26-29-13W

Total Depth. 4710'
Comm. 5-30-57 Comp. 6-22-57
Shot or Treated.
Contractor. Prime Drilling Co.
Issued. 6-21-58

County Pratt
KANSAS



Elevation. 1894' DF

Production. 40 BOPD

CASING:

10 3/4" 377' cem w/300 sx.
7" 4702' cem w/100 sx.

Figures Indicate Bottom of Formations.

sand	160
sand & shale	195
shale & sand streaks	225
shale, shells & red rock	300
red rock	377
red bed & shells	770
shale & anhydrite	850
shale & shells	1620
shale & lime	1880
lime w/sandy streaks	2010
lime & shale	2130
lime	2290
sandy lime	2320
lime & shale	3335
lime	3645
lime & shale	3725
sandy shale & lime	3815
lime	4480
lime cherty streaks	4540
lime & chert	4552
lime	4580
dolomite & chert	4599
shale sand dolomite	4612
sand	4615
shale	4620
sand	4624
shale	4635
shale & sand	4670
sandy lime	4690
sand & shale	4695
lime	4703 RTD
lime	4710
Total Depth	

TOPS: SCOUT

Topeka (scout)	3325
Heebner	3709
Douglas	3743
Brown Lime	3891
Lansing	3904
Mississippi	4373
Kinderhook	4410
Viola	4470
Simpson	4590
Simpson Sand	4607
Arbuckle	4692

7-20-57 perf. 4608-12'