


H.F. WILCOX OIL & GAS CO.
W.H. Hirmon No. 1

SEC. 30 T. 2 R. 1W
CSE NW

Total Depth: 3565'
Comm. 12-21-40 Comp. 1-12-41
Shot or Treated.
Contractor. Helmerich & Payne, Inc.
Issued. 1-25-41

County. Republic



CASING:
15 1/2" 42'

Elevation.

Production. Dry

Figures Indioate Bottom of Formations.

surface clay	20	Plugging Record: Hole filled	
shale, shells, sand strks	120	to 300' of top with heavy	
sand	385	mud, bridge cemented with 20	
shale, shells, sand strks	640	sacks, filled with heavy mud	
shale & shells	810	to 10' of btm of cellar,	
shale	818	bridge cemented with 10	
anhydrite	975	sacks cement. This mud &	
lime	985	cement was pumped in the hole.	
shale & shells	1038		
chert	1040		
shale	1044		
chert	1048		
strks chert & shale	1050		
shale & shells	1125		
shale & strks lime	1300		
lime brkn & shale	1375		
shale & shells	1665		
shale & lime	1809		
lime	1816		
shale & lime shells	1880		
lime	1912		
lime & shale stringers	2007		
shale & lime	2107		
lime & strks shale	2190		
lime	2249		
shale & lime	2320		
lime & shale stringers	2403		
shale & lime	2472		
chert & lime	2533		
lime brkn & shale	2583	shale & lime shells	3376
shale	2688	shale	3394
Mississippi chat	2750	lime	3434
chat & lime	2844	lime hrd	3459
lime cherty	2897	lime, strks shale &	
chert & lime	2974	dolomite	3490
chert	2994	lime & strks shale	3517
chert & lime	3056	sand	3535
lime	3111	lime	3565
shale	3126	Total Depth.	
dolomite, lime, strks			
shale	3157		
sdv lime & strks shale	3242		
lime	3307		
shale	3312		
lime & shale strks	3350		

H.F. WILCOX OIL & GAS CO.
W.H. Hirmon No. 1

SEC. 30 T. 2 R. 1W
CSE NW

Total Depth: 3565'
Comm. 12-21-40 Comp. 1-12-41
Shot or Treated.
Contractor. Helmerich & Payne, Inc.
Issued. 1-25-41

County. Republic



CASING:
15 1/2" 42'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface clay	20
shale, shells, sand strks	120
sand	385
shale, shells, sand strks	640
shale & shells	810
shale	818
anhydrite	975
lime	985
shale & shells	1038
chert	1040
shale	1044
chert	1048
strks chert & shale	1050
shale & shells	1125
shale & strks lime	1300
lime brkn & shale	1375
shale & shells	1665
shale & lime	1809
lime	1816
shale & lime shells	1880
lime	1912
lime & shale stringers	2007
shale & lime	2107
lime & strks shale	2190
lime	2249
shale & lime	2320
lime & shale stringers	2403
shale & lime	2472
chert & lime	2533
lime brkn & shale	2583
shale	2688
Mississippi chat	2750
chat & lime	2844
lime cherty	2897
chert & lime	2974
chert	2994
chert & lime	3056
lime	3111
shale	3126
dolomite, lime, strks	
shale	3157
sdy lime & strks shale	3242
lime	3307
shale	3312
lime & thin strks shale	3356

Plugging Record: Hole filled
to 300' of top with heavy
mud, bridge cemented with 20
sacks, filled with heavy mud
to 10' of btm of cellar,
bridge cemented with 10
sacks cement. This mud &
cement was pumped in the hole.

shale & lime shells	3376
shale	3394
lime	3434
lime hrd	3459
lime, strks shale & dolomite	3490
lime & strks shale	3517
sand	3535
lime	3565
Total Depth.	