


WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY  
412 Union National Bk Bldg., Wichita, Kansas

CARTER OIL CO.  
Eltiste No. 1.

SEC. 35      T. 2      R. 19 W  
CSE NE

Total Depth. 3545'  
Comm. 9-8-41      Comp. 10-10-41  
Shot or Treated.  
Contract cr.  
Issued.      11-22-41

County.      Phillips



CASING:

8 5/8"      258'  
5 1/2"      3410'

Elevation.

Production.      Pot. 426 B.

Figures Indicate Bottom of Formations.

|                    |           |
|--------------------|-----------|
| clay               | 40        |
| shale & shell      | 190       |
| shale & sand       | 264       |
| shale & shell      | 827       |
| sand               | 836       |
| shale & shell      | 887       |
| lime               | 891       |
| shale & shell      | 990       |
| lime               | 1003      |
| shale              | 1065      |
| lime, shale, sand  | 1206      |
| sand               | 1250      |
| shale gy & shell   | 1355      |
| shale red & shell  | 1532      |
| anhydrite          | 1558      |
| shale              | 1650      |
| shale & shell      | 1768      |
| shale              | 2215      |
| lime               | 2263      |
| lime brkn          | 2314      |
| shale              | 2337      |
| lime brkn          | 2442      |
| lime               | 2478      |
| shale              | 2490      |
| shale & iron strks | 2544      |
| shale              | 2653      |
| lime               | 2672      |
| shale & lime strks | 2763      |
| lime sdy strks     | 2764      |
| shale              | 2770      |
| shale & lime       | 2830      |
| lime               | 2893      |
| shale              | 2907      |
| lime sdy           | 2933      |
| lime               | 3395      |
| cored 3395-3405    |           |
| sand               | 3405-3417 |
| shale & lime strks | 3455      |
| shale              | 3460      |
| lime               | 3474      |
| shale & lime strks | 3491      |
| lime               | 3497      |
| shale              | 3511      |
| lime               | 3516      |
| shale              | 3525      |
| lime               | 3545      |
| Total Depth.       |           |

Acid:

500, 1000, 500, 500, 1000,  
1000, and 500 Gals.

Perforated 3347 $\frac{1}{2}$ -55

Ripped Pipe 3328 $\frac{1}{2}$ -33

Squeezed off 3284-88 & 3265-70

Ripped Pipe 3250-55, 3231-38,  
3211 $\frac{1}{2}$ -22, and 3176-86