

Geological Report

KCC
OCT 26 2010
CONFIDENTIAL

American Warrior Inc.
Hoover #1-17
335' FSL & 2584' FWL
Sec. 27 T2S R24W
Norton County, Kansas

Ed Glassman
Geologist

RECEIVED
OCT 26 2010
KCC WICHITA

American Warrior, Inc.

General Data

Well Data:

American Warrior Inc.
Hoover #1-17
E/2-SE-SE-SW
335' FSL & 2584' FWL
Sec. 27 T.2S R.24 W.
Norton County, Kansas
API # 15-137-20, 530-0000

Drilling Contractor:	Mallard Drilling Co
Spud Date:	9/25/2010
Rotary TD Date:	10/02/2010
Rotary TD:	3760'
Elevation:	2474' Ground Level 2479' Kelly Bushing
Casing:	Surface 205' 8 5/8" 24# surface casing
Samples:	10' wet and dry, 3800' to RTD
Drilling Time:	3700' to RTD
Electric Logs:	None
Drillstem Tests:	One
Problems:	None

Formation Tops

RECEIVED
OCT 25 2010
KCC WICHITA

Hoover 1-17

Stone Corral 2036'+443
Base Stone Corral 2065'+414
RTD 3760'-1281

KCC
OCT 26 2010
CONFIDENTIAL

DST 1 3540' to 3483' Interval 43' LKC

IF	No Blow	IFP 13.29# -14.6#
ISI	No Blow	ISP 80.47#
FF	No Blow	FFP 14.6# -15.4#
FSI	No Blow	FSP 55.23#

Recovery: 5' M

Summary: Due to structural position and lack of commercial oil shows in tests, the decision was made to plug & abandon the Hoover 1-17.

Respectfully Submitted,
Ed Glassman

RECEIVED
OCT 26 2010
KCC WICHITA