

12-508W 84  
 MAP NO. 84 SEC. 18 TWP. 30S RGE. 33W

STATE Kans COUNTY Haskell LOC. C NE SW

OPERATOR Pan American FT. FROM \_\_\_\_\_ LINE \_\_\_\_\_

WELL NO. 1 FARM NAME C. R. Anton "A" FT. FROM \_\_\_\_\_ LINE \_\_\_\_\_


Lemon, North ELEV. 2953 GR. 2959 DF. 2963 KB

FR. 11/1/62 SPUD 11/1/62 COMP. 12/11/62

CONT. Big Chief Tools /GEOL. \_\_\_\_\_

NAME PRODUCING INTERVAL COMPLETION RECORD FROM - TO PERF. W/HOLES TREATMENT RECORD

a	_____	_____	_____	_____
b	_____	_____	_____	_____
c	_____	_____	_____	_____
d	_____	_____	_____	_____



a I. P. OIL/DIST. \_\_\_\_\_ WTR. \_\_\_\_\_ GAS \_\_\_\_\_ M.C.F.P.D. \_\_\_\_\_ CHK. \_\_\_\_\_ HRS. \_\_\_\_\_

b " " " " " " " " " "

c " " " " " " " " " "

d \_\_\_\_\_

D & A

D & A ( )

SIP# \_\_\_\_\_ FI TP # \_\_\_\_\_ FI CP# \_\_\_\_\_ SIBHP \_\_\_\_\_

GOR. \_\_\_\_\_ GR. \_\_\_\_\_ PBTD \_\_\_\_\_ TD 5006

CASING - CEMENT RECORD

SIZE	DEPTH	W/SAX.	SIZE	DEPTH	W/SAX.
<u>5/8"</u>	<u>@ 738</u>	<u>500</u>			
<u>1/2"</u>	<u>@ 4999</u>	<u>210</u>			

OPERATOR Pan American WELL NO. 1 C. R. Anton "A" ELEV. 2963 KB

SAMPLE TOPS	DEPTH	SUB SEA	ELEC. TOPS	DEPTH	SUB SEA
KB Tops & Datums:					
RTD (Chero)	5006	-2043	Chase	2606	+ 357
			CG	2900	+ 63
RTD 5006, Log,			Penn	3438	- 475
WLT #1 (Des M) 4792-93', Op 1 hr,			Tor	4071	-1108
R 960' cc Wtr, IBHP 50#/15",			Mo	4124	-1161
SP 50#, FBHP 1280#/20".			Lans "A"	4143	-1180
WLT #2 (Lans) 4195-96', Op 70",			KC "A"	4603	-1640
R .52 Cfg (Shot), IBHP 50#/NT,			Des M	4769	-1806
SP 50#, FBHP 50#. NT, 5 1/2" @			Chero	4936	-1973
4999' w/210 sx, Perf 8/4792-94			LTD	N.A.	
(Des M) 500 A, \$ Ld, \$ 1/2 BO +					
BWPH/5 hrs, 1000 A, \$ Ld, \$ 1/2 BWPH w/SSO/3 hrs, PB 4740, Perf					
8/4195-97 (Lans) \$ dry, 750 A, \$ Ld, \$ 9 BW w/SSO/5 hrs, 2000 A,					
R Ld, \$ 7 BWPH/4 hrs, PB 4180, 8/4151-53 (Lans) \$ 37 BLW/6 hrs,					
\$ 60 BW w/Scum Oil/NT, Pull pipe, D & A (12/4/62)					

COMPLETED

Amarillo  
Lsg - 1180  
MVM - 1806  
~~220~~

LIBERAL ELECTRIC LOG TOPS

2963 KB

- Winfield 2677 (+286)
- Council Grove 2920 (+43)
- Heebner 4050 (-1087)
- Toronto 4070 (-1107)
- Lansing 4143 (-1180) \$ 60 BW w/scum oil/NT
- "A-1" 4192 (-1229) \$ 8 BW w/SSO/5 hrs
- "D" 4602 (-1639)
- Marmaton 4769 (-1806) \$  $\frac{1}{2}$  BWPB w/SSO/3 hrs.
- TD 5006 D & A