WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY

UNION NATIONAL BANK BLDG, WICHITA KANSAS

20993

Location C NW/4 NE/4 Sec. 35 T. 30 R. 2W.

Casing Record

10" 586
20" 8¼" 1534
15½" 65/8" 1857
12½" 133 53/16"

County- Sumner.
Farm- Frantz No. 3
Company- De Forcest Drlg. Co.
Contr.-
Comm.- 12/18/1928. Comp.- 1/26/1929.
Total Depth 2115' Shot Quarts Between
Correspondence Regarding This Well Should Be Referred to



Elevation

Figures Indicate Bottom of Formations. Initial Production Dry.
Date Issued. 4/20/1929.

| Formation | Depth |
|---|---|
| light mud soft | 26 |
| shale blue soft | 65 |
| red rock soft | 75 |
| HFW 60 to 65 | |
| shale blue soft | 230 |
| red rock soft | 235 |
| shale blue soft | 295 |
| salt soft | 330 |
| shale blue soft | 335 |
| shale white soft | 340 |
| salt light soft | 440 |
| shale blue soft | 445 |
| lime white hard | 460 |
| shale light soft | 465 |
| lime grey hard | 470 |
| shale blue soft | 475 |
| hole caving., | |
| lime shells soft | 505 |
| shale dark | 510 |
| lime white hard | 520 |
| shale and shells light soft | 535 |
| lime grey hard | 550 |
| lime white hard | 570 |
| shale white soft | 580 |
| lime grey hard | 599 |
| SLM 598 | |
| shale blue soft | 605 |
| lime brown hard | 640 |
| shale grey soft | 670 |
| lime white hard | 705 |
| shale blue soft | 725 |
| lime grey hard | 765 |
| shale white soft | 780 |
| red rock soft | 795 |
| lime white hard | 825 |
| shale blue soft | 835 |
| lime white hard | 895 |
| sdy shale light soft | 905 |
| 1BW 920-925 | |
| broken lime br soft | 920 |
| lime white hard | 940 |
| slate white soft | 950 |
| red rock | 955 |
| lime white hard | 965 |
| shale blue soft | 975 |
| lime white hard | 985 |
| shale blue soft | 995 |
| lime white hard | 1020 |
| sand grey soft | 1030 |
| 3BW 1020-1025 | |
| lime white hard | 1035 |
| red rock | 1050 |
| lime white hard | 1060 |
| shale blue soft | 1100 |
| lime white hard | 1110 |
| shale blue soft | 1120 |
| lime white hard | 1125 |
| shale blue soft | 1155 |
| lime white hard | 1175 |
| shale blk soft | 1185 |
| lime white hard | 1200 |
| shale blue soft | 1205 |

| Formation | Depth. |
|---|---|
| red rock soft | 1215 |
| lime white hard | 1225 |
| shale blue soft | 1230 |
| lime white hard | 1260 |
| shale blk soft | 1270 |
| lime grey hard | 1290 |
| shale blue soft | 1295 |
| lime white hard | 1300 |
| shale dark soft | 1310 |
| lime grey hard | 1350 |
| shale blue soft | 1355 |
| lime shells | 1405 |
| shale light soft | 1415 |
| lime white hard | 1420 |
| shale dark soft | 1440 |
| lime white hard | 1450 |
| shale blue soft | 1520 |
| SLM 1534 | |
| shale blue soft | 1550 |
| lime white hard | 1560 |
| shale blue soft CAVE | 1595 |
| lime brown hard | 1630 |
| 2BW 1600 to 1610 | |
| shale blk soft | 1650 |
| shale dark | 1680 |
| shale and shells hard | 1725 |
| lime brown hard | 1730 |
| shale dark soft | 1750 |
| lime white hard | 1790 |
| shale and shells dark soft | 1825 |
| shale light soft | 1840 |
| lime white hard | 1842 |
| shale dark soft | 1850 |
| lime grey hard | 1858 |
| shale blue soft | 1865 |
| lime grey hard | 1875 |
| shale and shells | 1912 |
| shale blue soft | 1927 |
| lime white hard | 1975 |
| hole caving some. | |
| shale white soft | 1990 |
| sdy lime white hard | 2005 |
| sdy shale light soft | 2026 |
| lime grey hard | 2034 |
| ½ BW 2015-2020 | |
| shale sdy light soft | 2064 |
| lime white hard | 2095 |
| HFW | |
| water sand white soft | 2115 |
| TD. | |