

Geological Report

American Warrior Inc.
Esplund #1-19
1998' FSL & 601' FEL
Sec. 19 T30S R23W
Clark County, Kansas

James Dilts
Geologist

RECEIVED
JUN 08 2010
KCC WICHITA

American Warrior, Inc.

General Data

Well Data: American Warrior Inc.
Esplund #1-19
NE-NE-SE
1998' FSL & 601' FEL
Sec. 19 T.30S R.23 W.
Clark County, Kansas
API # 15-025-21, 394-0000

Drilling Contractor: Murfin Drilling Co.

Spud Date: 2/19/2007

Rotary TD Date: 3/06/2007

Rotary TD: 5657'

Elevation: 2414' Ground Level
2426' Kelly Bushing

Casing: Surface 690' 8 5/8" 24# surface casing set at
690' w/ 300 sx Common
Production 5628' 5.5" 15.5# @5628' w/125 sx
SMD

Samples: 10' wet and dry, 4300' to RTD

Drilling Time: 4300' to RTD

Electric Logs: DIL/CDL//BHCS/CNL

Drillstem Tests: One

Problems: None

RECEIVED

JUN 08 2010

KCC WICHITA

Formation Tops

Esplund 1-19

Heebner	4408'-1924
Toronto	4418'-1992
Brown Lime	4568'-2142
Lansing	4584'-2158
Base KC	5061'-2635
Marmaton	5080'-2654
Pawnee	5162'-2736
Ft Scott	5114'-2688
Morrow Sd	5362'-2936
St Louis	5391'-2965

Summary: Due to structural position and log information, the decision was made to case the Esplund #1-19 for further evaluation.

Respectfully Submitted,

James F Dilts

RECEIVED
JUN 08 2010
KCC WICHITA