
WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company - STANOLIND OIL & GAS CO.
Farm - W.E.Davis "A" No. 1

SEC. 19 T. 30 R. 38W
SW SW NE
2790' NSL, 2790' E/1 of NE/4

Total Depth. 2622
Comm. 11-19-49 Comp. 12-12-49
Shot or Treated. acid
Contractor.
Issued. 2-11-50

County. Grant
KANSAS



Elevation. 3150 Grd.

Production. 12,237,000 gas

CASING:
10 3/4 " 575' cem w/350 sx.
7" 2577' cem w/1100 sx.

Figures Indicate Bottom of Formations.

surface clay, sand	340
sand	400
sand, shale	515
red bed	800
redbed, sand, shells	1350
sand, shale	1430
gyp, red bed	1670
redrock, gyp, anhyd.	1755
anhyd., gyp	2185
anhyd., shale	2245
anhyd., gyp	2275
anhyd., gyp, shale	2323
anhyd., shale	2356
anhyd., gyp	2400
anhyd., lime	2425
anhyd., shale	2490
lime, shale	2545
lime	2622
Total depth	

Tops:

Hollenberg	2326-2376
Herington-Krider	2388-2440
Winfield	2458-2492
Towanda	2526-2552
Ft. Riley(top)	2577

Rotary total depth 2612'

Schlumberger to 2622 total depth

Acid:
Acid Engr. as follows:
Ft. Riley w/1000 gals 15%.
Hollenberg w/500 gals 15%.
Herington-Krider w/1000 gals 15%.
Winfield w/1000 gals 15%.
Towanda w/1000 gals 15%.
All zones w/33,000 gals 15%.

Lane Wells jet perforated w/4 SPF as follows:

Hollenberg	2364-2376
Herfington-Krider	2388-2440
Winfield	2458-2492
Towanda	2526-2552