

36-31-41W⁸⁴
KCC
P1

TYPE ✓

AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

Compt. _____

SIDE ONE

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD

Amount and kind of material used		Depth interval treated
Acidize w/500 gals 15% MCA Acid.		3714 - 3718
Acidize w/2100 gals 15% gelled acid & 2100 gals gelled KCL flush w/lease crude		3714 - 3718
Date of first production May 16, 1984	Producing method (flowing, pumping, gas lift, etc.) pumping	Gravity 35
Estimated Production - I.P. 80 bbls.	Gas _____ MCF	Water % 3 bbls.
Disposition of gas (vented, used on lease or sold) used on lease		Gas-oil ratio _____ CFPB
Perforations 3714 - 3718		

LICENSE # 5050 EXPIRATION DATE 6-85

OPERATOR Hummon Corporation API NO. 15-007-21,800

ADDRESS 400 One Main Place COUNTY Barber

Wichita, KS 67202 FIELD McRenolds SW

** CONTACT PERSON Wilber Berg PROD. FORMATION Douglas

PHONE 263-8521 Indicate if new pay.

PURCHASER Getty Trading & Transportation LEASE Chapin ✓

ADDRESS P.O. Box 5568 WELL NO. 4-36

Denver, Colorado 80217 WELL LOCATION 150' SE/C SW NW

DRILLING Big-H Drilling, Inc. 810 Ft. from west Line and

CONTRACTOR 400 One Main Place 1980 Ft. from north Line of

ADDRESS Wichita, KS 67202 the NW (Qtr.) SEC 36 TWP 31 RGE 11 (W).

PLUGGING N/A WELL PLAT (Office Use Only)

CONTRACTOR _____

ADDRESS _____

TOTAL DEPTH 3880 PBD 3830'

SPUD DATE 4-13-84 DATE COMPLETED 4-21-84

ELEV: GR 1660 DF 1670 KB 1673

DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE C-21,045

Amount of surface pipe set and cemented 210.50 DV Tool Used? No

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) Oil Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion. Other completion. NGPA filing.

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T

Wilber Berg, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. statements and allegations contained therein are true and correct.

MAY 8 9 1985
State Geological Survey
WICHITA BRANCH

WELL PLAT				(Office Use Only)
				KCC
				KGS ✓
				SWD/REP
				PLC
RELEASED				NGPA
Date: MAY 2 1985				
FROM CONFIDENTIAL				

W11-1E-2E

ACO-1 Well History

Side TWO

OPERATOR Hummon Corporation LEASE NAME Chapin SEC 36 TWP 31 RGE 11 (W)

WELL NO 4-36

FILL IN WELL INFORMATION AS REQUIRED;

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Show Geological markers, logs run, or other Descriptive information.

Formation description, contents, etc. Top Bottom Name Depth

<p>Check if no Drill Stem Tests Run. <input checked="" type="checkbox"/> Check if samples sent Geological Survey.</p> <p>DST #1: 3695-3726' OP 45-60-45-60 GTS 20 min., 30 min. ga. 97,800 CFG 45 min. ga. 47,000 CFG 2nd OP after 10 min. ga. 24,500 CFG 20 min. ga. 15,400 CFG, 30 min. ga. TSTM Rec. 1430' GO 660' HO&GCM SIP 1158-1131 HP 1814-1814 FP 139-279/363-461 BHT 105°</p> <p>DST #2: 3727-3754' OP 30-50-45-60 GTS 7 min. ga, 147 MCFG in 10 min. after 20 min. 177 MCFG, 30 min. 189 MCFG 2nd OP ga. 526 MCFG, after 10 min. 526 MCFG after 20 min. 472 MCFG, 30 min. 415 MCFG, 45 min. 415 MCFG Rec. 60' GCM, 180' GCMW, 120' GW SIP 1378-1322, FP 253-225/281-197, HP 2050-1826</p> <table border="0"> <tr><td>Sand</td><td>0</td><td>40</td></tr> <tr><td>Red Rock</td><td>40</td><td>104</td></tr> <tr><td>Red Beds</td><td>104</td><td>228</td></tr> <tr><td>Red Beds & Shale</td><td>228</td><td>1252</td></tr> <tr><td>Shale & Lime</td><td>1252</td><td>3004</td></tr> <tr><td>Lime & Shale</td><td>3004</td><td>3185</td></tr> <tr><td>Shale & Lime</td><td>3185</td><td>3500</td></tr> <tr><td>Lime & Shale</td><td>3500</td><td>3650</td></tr> <tr><td>Shale & Lime</td><td>3650</td><td>3726</td></tr> <tr><td>Lime, Shale & Sd.</td><td>3726</td><td>3754</td></tr> <tr><td>Shale & Lime</td><td>3754</td><td>3808</td></tr> <tr><td>Lime & Shale</td><td>3808</td><td>3880</td></tr> </table> <p>If additional space is needed use Page 2</p>	Sand	0	40	Red Rock	40	104	Red Beds	104	228	Red Beds & Shale	228	1252	Shale & Lime	1252	3004	Lime & Shale	3004	3185	Shale & Lime	3185	3500	Lime & Shale	3500	3650	Shale & Lime	3650	3726	Lime, Shale & Sd.	3726	3754	Shale & Lime	3754	3808	Lime & Shale	3808	3880				<p>ELECT. LOG TOPS</p> <table border="0"> <tr><td>Ind. Cv.</td><td>2676</td><td>-1003</td></tr> <tr><td>Tark Lm</td><td>2873</td><td>-1200</td></tr> <tr><td>Elgin Sh</td><td>3488</td><td>-1815</td></tr> <tr><td>Heebner</td><td>3654</td><td>-1981</td></tr> <tr><td>Dgls Lm</td><td>3703</td><td>-2030</td></tr> <tr><td>Dgls Sh</td><td>3724</td><td>-2051</td></tr> <tr><td>Lansing</td><td>3850</td><td>-217</td></tr> <tr><td>LTD</td><td>3878</td><td></td></tr> </table>	Ind. Cv.	2676	-1003	Tark Lm	2873	-1200	Elgin Sh	3488	-1815	Heebner	3654	-1981	Dgls Lm	3703	-2030	Dgls Sh	3724	-2051	Lansing	3850	-217	LTD	3878	
Sand	0	40																																																														
Red Rock	40	104																																																														
Red Beds	104	228																																																														
Red Beds & Shale	228	1252																																																														
Shale & Lime	1252	3004																																																														
Lime & Shale	3004	3185																																																														
Shale & Lime	3185	3500																																																														
Lime & Shale	3500	3650																																																														
Shale & Lime	3650	3726																																																														
Lime, Shale & Sd.	3726	3754																																																														
Shale & Lime	3754	3808																																																														
Lime & Shale	3808	3880																																																														
Ind. Cv.	2676	-1003																																																														
Tark Lm	2873	-1200																																																														
Elgin Sh	3488	-1815																																																														
Heebner	3654	-1981																																																														
Dgls Lm	3703	-2030																																																														
Dgls Sh	3724	-2051																																																														
Lansing	3850	-217																																																														
LTD	3878																																																															

Report of all strings set — surface, intermediates, production, etc.

CASING RECORD (New) ~~XXXXXXXX~~

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs./ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 1/4	8-5/8	23#	224	Common	215	2% gel 3% cc
Production	7 7/8	5-1/2	14#	3872	60-40 Poz	100	10% salt, 3/4 of 1% D31 5# gils. per sx., 12bb. mud sweep ahead

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
			4 shots/ft	SSB	3714 - 3718

Size	Setting depth	Packer set at
2-3/8	3753'	